



CEILING TILE PAINT

#20-51 New White, #20-52 Old White

A special water based formulation for touching up stains that appear on both textured and acoustical ceiling tiles. Must be used in an upright position and is activated by tipping sprayhead to the side. For ease of application, Seymour's Spray Wand #Z-606 (33" extension) or Stripe Gun #Z-605 may be used.

Suggested Uses:

All fiber type ceiling tiles
Air conditioning vents

Benefits:

Fast dry
Maintains acoustic properties
Easy over-head application
Matches color of tile
Will not warp or sag tiles

Packaging:

UPC Code	20-51: 043281001779 20-52: 043281001786
Cans per case	12
Shipping weight per case	18 lbs.
Container	20 fluid ounce can
Label weight	16 ounces (454 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Flammable"
Flash point	-4F
Specific Gravity	0.83
Solids Content	~22%
VOC content	~57%, cannot exceed 60%
MIR value	~1.13, cannot exceed 1.20
HAPs content	~16%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Fair
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 15 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code
--------	-------------	----------