830-2009 CAL-TINT® RAW UMBER

Specification: 000000139779 Revision Date: 07-18-2022



Version Number: 04

1. Identification

Product identifier 830-2009 CAL-TINT® RAW UMBER

Other means of identification

SAP Specification 000000139779

Recommended use Aqueous colorant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Chromaflo Technologies Corporation

2600 Michigan Avenue

Ashtabula, OH, USA 44005-0816

Canadian facility Chromaflo Technologies Canada

235 Orenda Road

Brampton, Ontario, Canada L6T-1E6

US telephone 440-997-5137 **Canadian telephone** 905-451-3810

NA: EMERGENCY # (3E) 866-519-4752 **GLOBAL: EMERG. # (3E)** (+1) 760-476-3962

3E CONTRACT # 12154 **3E ACCESS CODE** 334294

CANADA: CANUTEC 613-996-6666

EMERGENCY NUMBER

Product Regulatory

Services

ehs americas@chromaflo.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling. Take off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information If product is in liquid or paste form, hazards related to dust are not considered significant. But

product may contain substances that could be potential hazards if caused to become airborne

due to abrasive processes.

Material name: 830-2009 CAL-TINT® RAW UMBER

000000139779 Version #: 04 Revision date: 07-18-2022 Issue date: 02-28-2017

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------------|--------------------------|------------|---------|
| Iron Oxide | | 1309-37-1 | 15 - 40 |
| ethanediol; ethylene glycol | | 107-21-1 | 10 - 30 |
| Talc, Magnesium silicate hydrate | | 14807-96-6 | 7 - 13 |
| Manganese trioxide | | 1317-34-6 | 5 - 10 |
| Calcium Carbonate | | 1317-65-3 | 1 - 5 |
| Carbon Black | | 1333-86-4 | 1 - 5 |
| Diethylene glycol | | 111-46-6 | 1 - 5 |
| Silica, crystalline (quartz) | | 14808-60-7 | 0.1 - 1 |
| Other components below reportable | levels | | 15 - 40 |

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eve contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

the chemical

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Special protective equipment

Specific hazards arising from

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the including any incompatibilities SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Limits for Air C Components | Туре | Value | Form |
|--|---------|-------------|----------------------|
| Calcium Carbonate (CAS 1317-65-3) | PEL | 5 mg/m3 | Respirable fraction. |
| , | | 15 mg/m3 | Total dust. |
| Carbon Black (CAS 333-86-4) | PEL | 3.5 mg/m3 | |
| ron Oxide (CAS 1309-37-1) | PEL | 10 mg/m3 | Fume. |
| /langanese trioxide (CAS 317-34-6) | Ceiling | 5 mg/m3 | |
| Silica, crystalline (quartz) CAS 14808-60-7) | PEL | 0.05 mg/m3 | Respirable dust. |
| JS. OSHA Table Z-3 (29 CFR 1910.1 | | | - |
| components | Туре | Value | Form |
| on Oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |
| ilica, crystalline (quartz) CAS 14808-60-7) | TWA | 0.1 mg/m3 | Respirable. |
| | | 2.4 mppcf | Respirable. |
| alc, Magnesium silicate ydrate (CAS 14807-96-6) | TWA | 0.1 mg/m3 | Respirable. |
| | | 20 mppcf | |
| | | 2.4 mppcf | Respirable. |
| IS. ACGIH Threshold Limit Values | | | |
| components | Туре | Value | Form |
| arbon Black (CAS 333-86-4) | TWA | 3 mg/m3 | Inhalable fraction. |
| thanediol; ethylene glycol CAS 107-21-1) | STEL | 10 mg/m3 | Aerosol, inhalable. |
| | | 50 ppm | Vapor fraction |
| | TWA | 25 ppm | Vapor fraction |
| on Oxide (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| langanese trioxide (CAS 317-34-6) | TWA | 0.1 mg/m3 | Inhalable fraction. |
| | | 0.02 mg/m3 | Respirable fraction. |
| Silica, crystalline (quartz) CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |
| alc, Magnesium silicate ydrate (CAS 14807-96-6) | TWA | 2 mg/m3 | Respirable fraction. |
| JS. NIOSH: Pocket Guide to Chemic | | | _ |
| components | Туре | Value | Form |
| Calcium Carbonate (CAS 317-65-3) | TWA | 5 mg/m3 | Respirable. |
| • | | 10 mg/m3 | Total |
| | | 10 mg/mo | 10101 |
| Carbon Black (CAS 333-86-4) | TWA | 0.1 mg/m3 | rotai |

| US. NIOSH: Pocket Guide to Cher Components | nical Hazards Type | Value | Form |
|--|----------------------------|------------|------------------|
| Manganese trioxide (CAS 1317-34-6) | STEL | 3 mg/m3 | Fume. |
| | TWA | 1 mg/m3 | Fume. |
| Silica, crystalline (quartz) (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable dust. |
| Talc, Magnesium silicate hydrate (CAS 14807-96-6) | TWA | 2 mg/m3 | Respirable. |
| US. Workplace Environmental Ex | posure Level (WEEL) Guides | | |
| Components | Туре | Value | |
| Diethylene glycol (CAS 111-46-6) | TWA | 10 mg/m3 | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.

Color Reddish-brown
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 1.6

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition No hazardous deco

products

No hazardous decomposition products are known.

Contact with incompatible materials.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

| Product | Species | Test Results | |
|--|---------|---------------------|--|
| 830-2009 CAL-TINT® RAV | V UMBER | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Rabbit | 51550 mg/kg | |
| Inhalation | | | |
| LC50 | Mouse | 65000 mg/l, 4 Hours | |
| Oral | | | |
| LD50 | Rat | 38 g/kg | |
| Components | Species | Test Results | |
| Carbon Black (CAS 1333-8 | 36-4) | | |
| <u>Acute</u> | | | |
| Oral | | | |
| LD50 | Rat | > 8000 mg/kg | |
| Diethylene glycol (CAS 111 | 1-46-6) | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Rabbit | 11890 mg/kg | |
| ethanediol; ethylene glycol (CAS 107-21-1) | | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Rabbit | 9530 mg/kg | |

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Iron Oxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

Silica, crystalline (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Talc, Magnesium silicate hydrate (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Silica, crystalline (quartz) (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4)

Silica, crystalline (quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

830-2009 CAL-TINT® RAW UMBER

Aquatic

Fish LC50 Fish 1456.4702 mg/l, 96 hours

Components Species Test Results

Diethylene glycol (CAS 111-46-6)

Aquatic Acute

Fish LC50 Western mosquitofish (Gambusia affinis) > 32000 mg/l, 96 hours

Trotter module (Gambabla ammo) C2000 mg/, Go notice

ethanediol; ethylene glycol (CAS 107-21-1)

Aquatic Acute

Fish LC50 Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diethylene glycol -1.47 ethanediol; ethylene glycol -1.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

 Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard and the Canadian Hazardous Products Regulation.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ethanediol; ethylene glycol (CAS 107-21-1) Manganese trioxide (CAS 1317-34-6)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Silica, crystalline (quartz) (CAS 14808-60-7)

Cancer

lung effects

Listed.

Listed.

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. | |
|---------------------|------------|----------|--|
| Ethylene glycol | 107-21-1 | 10 - 30 | |
| Manganese compounds | 1317-34-6 | 5 - 10 | |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethanediol; ethylene glycol (CAS 107-21-1) Manganese trioxide (CAS 1317-34-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

(ODIIA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon Black (CAS 1333-86-4)

ethanediol; ethylene glycol (CAS 107-21-1) Silica, crystalline (quartz) (CAS 14808-60-7) Talc, Magnesium silicate hydrate (CAS 14807-96-6)

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)
Ethanol; ethyl alcohol (CAS 64-17-5)
Listed: February 21, 2003
Listed: April 29, 2011
Listed: July 1, 1988

Silica, crystalline (quartz) (CAS 14808-60-7)

Listed: October 1, 1988
Talc, Magnesium silicate hydrate (CAS 14807-96-6)

Listed: April 1, 1990

California Proposition 65 - CRT: Listed date/Developmental toxin

Inventory name

ethanediol; ethylene glycol (CAS 107-21-1) Listed: June 19, 2015 Ethanol; ethyl alcohol (CAS 64-17-5) Listed: October 1, 1987

International Inventories

Country(s) or region

| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
|-----------------------------|--|-----|
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 02-28-2017

 Revision date
 07-18-2022

Version # 04

List of abbreviations AICIS: Australian Inventory of Industrial Chemicals.

DisclaimerThe information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use processing storage transportation, dispose

designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for

obtaining any required licenses.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: 830-2009 CAL-TINT® RAW UMBER

000000139779 Version #: 04 Revision date: 07-18-2022 Issue date: 02-28-2017 8 / 8

On inventory (yes/no)*