830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

Revision Date: 07-18-2022 Specification: 000000139782



Version Number: 03

1. Identification

Product identifier 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

Other means of identification

SAP Specification 000000139782 Recommended use Aqueous colorant **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Chromaflo Technologies Corporation Company

2600 Michigan Avenue

Ashtabula, OH, USA 44005-0816

Chromaflo Technologies Canada **Canadian facility**

235 Orenda Road

Brampton, Ontario, Canada L6T-1E6

US telephone 440-997-5137 905-451-3810 Canadian telephone

NA: EMERGENCY # (3E) 866-519-4752 GLOBAL: EMERG. # (3E) (+1) 760-476-3962

3E CONTRACT # 12154 334294 **3E ACCESS CODE**

613-996-6666 **CANADA: CANUTEC**

EMERGENCY NUMBER

Product Regulatory

Services

ehs americas@chromaflo.com

2. Hazard(s) identification

Not classified. Physical hazards **Health hazards** Carcinogenicity

OSHA defined hazards Not classified.

Label elements



Signal word

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Category 2

Response If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash

it before reuse.

Store locked up. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Talc, Magnesium silicate hydrate		14807-96-6	15 - 40
ethanediol; ethylene glycol		107-21-1	10 - 30
Diethylene glycol		111-46-6	3 - 7
Barium sulfate		7727-43-7	1 - 5
Polyoxyethylene nonylphenol branched ether phosphate sodium salt		68954-84-7	0.5 - 1.5
tributyl phosphate		126-73-8	0.5 - 1.5
Nonylphenoxypoly(ethyleneoxy)eth anol, branched		68412-54-4	0.1 - 1
Other components below reportable levels			30 - 60

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Specific methods

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW 000000139782 Version #: 03 Revision date: 07-18-2022 Issue date: 05-28-2017

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	aminants (29 CFR 1910.1000) Type	Value	Form
Barium sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
tributyl phosphate (CAS 126-73-8)	PEL	5 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910.1000)			_
Components	Туре	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Talc, Magnesium silicate hydrate (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
ethanediol; ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Talc, Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
tributyl phosphate (CAS 126-73-8)	TWA	5 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Chemical F	łazards		
Components	Туре	Value	Form
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.

Material name: 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

SDS US

US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	Form
		10 mg/m3	Total
Talc, Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
tributyl phosphate (CAS 126-73-8)	TWA	2.5 mg/m3	
		0.2 ppm	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
Diethylene glycol (CAS 111-46-6)	TWA	10 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Use a NIOSH/MSHA approved

respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Yellow.
Odor Mild.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and boiling

> 212 °F (> 100 °C)

range

Flash point 246.50 °F (119.16 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 1.4

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

	Product	Species	Test Results
--	---------	---------	--------------

830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

<u>Acute</u>

Dermal

LD50 Rabbit 36220 mg/kg

Inhalation

LC50 Rat 12300 mg/l, 6 Hours

Oral LD50

Rat 27 g/kg

Components Species Test Results

Diethylene glycol (CAS 111-46-6)

<u>Acute</u>

Dermal

LD50 Rabbit 11890 mg/kg

ethanediol; ethylene glycol (CAS 107-21-1)

<u>Acute</u>

Dermal

LD50 Rabbit 9530 mg/kg

tributyl phosphate (CAS 126-73-8)

Acute Dermal

DE0 D-

LD50 Rabbit > 3100 mg/kg

Inhalation

LC50 Rat 123 mg/l, 6 Hours

Material name: 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

SDS US

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity Talc, Magnesium silicate hydrate (CAS 14807-96-6)

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

Aquatic

Crustacea EC50 Daphnia 2224.2202 mg/l, 48 hours Fish LC50 Fish 754.1041 mg/l, 96 hours

Components **Species Test Results**

Barium sulfate (CAS 7727-43-7)

Aquatic

Acute

Crustacea EC50 Tubificid worm (Tubifex tubifex) >= 28.61 - <= 38.03 mg/l, 48 hours

Diethylene glycol (CAS 111-46-6)

Aquatic

Acute

Fish LC50 Western mosquitofish (Gambusia affinis) > 32000 mg/l, 96 hours

ethanediol; ethylene glycol (CAS 107-21-1)

Aquatic

Acute

LC50 Fish Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours

tributyl phosphate (CAS 126-73-8)

Aquatic

Acute

Fish LC50 Fathead minnow (Pimephales promelas) >= 1 - <= 10 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diethylene glycol -1.47 Partition coefficient n-octanol / water (log Kow)

-1.36 ethanediol; ethylene glycol tributyl phosphate

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code D005: Waste Barium

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the US Hazard Communication Standard

and the Canadian Hazardous Products Regulation.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans. Chemicals of Concern

Nonylphenoxypoly(ethyleneoxy)ethanol, branched

(CAS 68412-54-4)

Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action

Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium sulfate (CAS 7727-43-7) Listed. ethanediol; ethylene glycol (CAS 107-21-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard

Carcinogenicity

categories

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Ethylene glycol	107-21-1	10 - 30	
Poly(oxy-1,2-ethanediyl),	68412-54-4	0.1 - 1	
.alpha(nonylphenyl)omegahydroxy-, branched			

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethanediol; ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

ethanediol; ethylene glycol (CAS 107-21-1)

Nonylphenoxypoly(ethyleneoxy)ethanol, branched (CAS 68412-54-4)

Talc, Magnesium silicate hydrate (CAS 14807-96-6)

tributyl phosphate (CAS 126-73-8)

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Silica, crystalline (quartz) (CAS 14808-60-7) Listed: October 1, 1988 Talc, Magnesium silicate hydrate (CAS 14807-96-6) Listed: April 1, 1990

California Proposition 65 - CRT: Listed date/Developmental toxin

ethanediol; ethylene glycol (CAS 107-21-1) Listed: June 19, 2015

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

05-28-2017 Issue date 07-18-2022 **Revision date**

Version # 03

List of abbreviations AICIS: Australian Inventory of Industrial Chemicals.

Material name: 830-2024 CAL-TINT® EXTERIOR MEDIUM YELLOW

SDS US 000000139782 Version #: 03 Revision date: 07-18-2022 Issue date: 05-28-2017

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.