

Revision Number: 002.1 Issue date: 10/16/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: OSI Asphalt Tape
Product type: Flashing tape
Restriction of Use: None identified

None identified Region: United States
Contact information:

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 Telephone: +1 (800) 624-7767 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

1866180

### 2. HAZARDS IDENTIFICATION

WARNING: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE RESPIRATORY IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Avoid breathing dust or fumes. Wash thoroughly after handling. Use only outdoors or in a well-

ventilated area. Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

# See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous Component(s)	CAS Number	Percentage*	

Asphalt	8052-42-4	60 - 100
Extracts, petroleum, light paraffinic distillate solvent	64742-05-8	10 - 30

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Not hazardous by inhalation If symptoms are experienced, remove source of

contamination or move victim to fresh air.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

**Ingestion:** not relevant.

Symptoms: See Section 11.

Notes to physician: This product contains asphalt and process oil. Treat symptomatically and

supportively.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Dispose of according to Federal, State and local governmental regulations.

### 7. HANDLING AND STORAGE

Handling: Avoid prolonged or repeated skin contact with this material. Avoid eye contact.

Storage: Store in a cool, dry, well-ventilated area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Asphalt	0.5 mg/m3 TWA (as benzene solubles) Inhalable fraction.	None	None	None
Extracts, petroleum, light paraffinic distillate solvent	None	5 mg/m3 PEL Mist.	None	None

Engineering controls: General room ventilation is usually adequate.

**Respiratory protection:**No personal respiratory protective equipment normally required.

**Eye/face protection:** None required in normal use.

**Skin protection:** Neoprene or oil resistant gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:SolidColor:BlackOdor:tar-likeOdor threshold:Not available.pH:Not available.Vapor pressure:Not available.Boiling point/range:Not available.

**Melting point/ range:** 85.0 - 132.2 °C (185°F - 270°F)

Specific gravity: 1.0 - 1.1

Vapor density: Not available.

Flash point: > 232.2 °C (> 449.96 °F) Certificate of Supplier; Product is a solid.

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. **Evaporation rate:** Not available. Solubility in water: Negligible Partition coefficient (n-octanol/water): Not available. **VOC** content: Negligible Viscosity: Not available. **Decomposition temperature:** Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

products:

Hazardous decomposition Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Incompatible materials: Strong oxidizing agents. Strong bases.

Reactivity: Not available.

**Conditions to avoid:** Avoid excessive heat and ignition sources.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Eyes, Skin

#### Potential Health Effects/Symptoms

**Inhalation:** Not a hazard under normal conditions of use. May irritate the nose and respiratory system.

Skin contact: Repeated contact may cause skin irritation

Eye contact: May cause slight irritation to eyes on contact.

Ingestion: Not a likely route of entry. No significant adverse effects are expected upon ingestion of the

product.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Asphalt	None	Central nervous system, Irritant, Respiratory
Extracts, petroleum, light paraffinic distillate solvent	None	Irritant, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Asphalt	No	Group 2B	No
Extracts, petroleum, light paraffinic distillate solvent	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:**Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

IDH number: 1866180 Product name: OSI Asphalt Tape

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 10/16/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1866180 Product name: OSI Asphalt Tape