



CRAFTSMEN QUALITY STAINS AND FINISHES SINCE 1953.

TECHNICAL DATA SHEET

OLD MASTERS® CRYSTAL CLEAR PASTE WAX

AVAILABLE SIZES: One Pound containers

PRODUCT CODES: 30901

PRODUCT DESCRIPTION: Old Masters® Paste Wax is formulated with imported Carnauba, the hardest natural wax known to man. It provides outstanding durability while enhancing the beauty of floors, furniture and woodwork. This product does not contain beeswax or silicone.

DIRECTIONS FOR USE: All surfaces must be clean, dry and free from dirt, wax, grease, glue and other contaminants. Apply wax evenly with a clean, lint-free cloth. A thin coating produces the best results. Allow wax to dry thoroughly before polishing. On new surfaces, a second application is recommended. Not recommended for asphalt tile.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

HELPFUL HINTS: Thin coats dry faster and harder than thick ones. It is important that each coat be completely dry before applying the next one. If a soft layer is trapped beneath the top one, it will never harden.

Don't use on asphalt or rubber tile floors. Solvents in this product can soften these flooring materials. Keep away from heat, sparks and open flame. Use adequate ventilation. Avoid prolonged or repeated contact with skin.

TECHNICAL DATA

SOLIDS BY WEIGHT:	20.0%	FLASH POINT:	102°F Tag Closed Cup
SOLIDS BY VOLUME:	20.0%	VISCOSITY AT 77 °:	Gel
V.O.C.:	Not applicable	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	15 to 30 minutes
THEORETICAL COVERAGE @ Mil DFT:	1600 sq. ft. per gallon	RECOMMENDED THINNER:	Do no thin. Use as packaged.
COVERAGE @ RECOMMENDED DFT	Not Applicable		
RECOMMENDED DFT PER COAT:	Not Applicable		
WEIGHT PER GALLON:	6.4 lbs		

Limited Warranty Since Old Masters® does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed the replacement of the product.