

## TECHNICAL DATA SHEET

### OLD MASTERS<sup>®</sup> 100% PURE TUNG OIL

AVAILABLE SIZES: Pint (08), Quart (04) and Gallon (01)

PRODUCT CODES: 90008 Pint

90004 Quart

90001 Gallon

**PRODUCT DESCRIPTION:** Old Masters 100% Pure Tung Oil creates a beautiful, hand rubbed finish. Ideal for use on antiques, fine furniture or bare wood. This product provides a durable water and alcohol resistant oil finish. Tung Oil is formulated to be absorbed into wood, creating a finish that will not crack, chip or peel.

**SURFACE PREPARATION:** All surfaces must be clean, dry and free from dirt, wax, grease, glue and other contaminants or penetration and adhesion will be affected.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

- APPLICATION:**
1. Apply Old Masters 100% Tung Oil with a lint-free cloth or by hand. On large surfaces or in high humidity, thinning with mineral spirits will improve application. Up to one (1) part mineral spirits to one (1) part Tung Oil may be used; however, thinning beyond this ratio will result in noncompliance with VOC regulations.
  2. When the entire area has been coated, wipe off excess oil with a soft, lint-free cloth.
  3. If a second coat is desired, allow the first coat to dry (about 12 hours), then rub down with 0000 steel wool.
  4. Repeat steps 1 and 2. Do not apply more coats than the wood can absorb.

**THINNING:** Up to one (1) part mineral spirits to one (1) part Tung Oil may be used; however, thinning beyond this ratio will result in noncompliance with VOC regulations.

**CLEAN UP:** Using a cleaning solvent, such as paint thinner or mineral spirits, is recommended for clean up. The use of paint thinners or mineral spirits may violate VOC compliancy in your area. Check with your local government agencies to ensure proper compliancy.

To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

**MAX VOC:** 8 g/L (0.1 lbs/gal)

## TECHNICAL DATA SHEET

### OLD MASTERS<sup>®</sup> 100% TUNG OIL

#### TECHNICAL DATA

SOLIDS BY WEIGHT:	99.0%	FLASH POINT:	400°F Tag Closed Cup
SOLIDS BY VOLUME:	99.0%	VISCOSITY AT 77 °:	53 sec. #2 Zahn Cup
V.O.C.:	8 grams/liter	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	Approximately 8 to 12 hours
THEORETICAL COVERAGE @ Mil DFT:	300-400 sq. ft. per gallon	VEHICLE:	Oil
COVERAGE @ RECOMMENDED DFT	Not Applicable	RECOMMENDED THINNER:	Mineral Spirits
RECOMMENDED DFT PER COAT:	Not Applicable		
WEIGHT PER GALLON:	7.85 lbs/gal		

Limited Warranty Since Old Masters<sup>®</sup> does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters<sup>®</sup> liability will under no circumstances exceed the replacement of the product.