



MULTI-SURFACE SEALER & STAINBLOCKER

NO. 2000



PRODUCT INFORMATION

KILZ 2™ ALL-PURPOSE Primer is a fast drying, water-based, multi-surface primer-sealer-stainblocker with excellent adhesion, mildew resistance, sealing properties and very mild odor. KILZ 2 ALL-PURPOSE Primer blocks medium stains including mineral water stains, rust, grease, ink, pencil and felt marker. Enhanced hiding makes it ideal for changing colors and helps lessen the number of coats of paint required. Use under or over water-based or oil-based paints. Not recommended on flooring.

RECOMMENDED USES:

Use on properly prepared interior and exterior surfaces, such as:

- Wood
- Stucco
- Paneling
- Drywall
- Brick
- Painted Metal
- Plaster
- Masonry
- Galvanized Metal

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 2000 128 oz / 2 oz

Sheen: < 10.0 @ 85°

Sheen levels depend on porosity and various surface irregularities.

Resin Type: Acrylic Polymer

Weight per Gallon: 11.0 lbs

% Solids by Volume: 33%

% Solids by Weight: 48.5%

VOC: < 50 g/L

Flash Point: N/A

Viscosity: 95 – 105 KU

Recommended Film Thickness:

Wet: 5.3 mils / Dry: 1.7 mils @ 300 sq ft/gal

Wet: 4.0 mils / Dry: 1.3 mils @ 400 sq ft/gal

Coverage: 300 – 400 sq ft/gal depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon / Polyester

Roller: 3/8" – 3/4" nap

Airless Spray: Fluid pressure of 1,800 – 3,000 psi

Tip: .015" – .021"

Filter: 60 mesh

Thinning: Not recommended. Product is formulated for use at package consistency only.

Dry Time: @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 Minutes

To Recoat: 1 hour

SURFACE PREPARATION:

The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.*

Unpainted, exterior wood: Exposed to sun and/or moisture longer than 2 – 4 weeks must be cleaned and sanded before priming.*

Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.

Masonry, Brick, Stucco and Plaster: KILZ 2 ALL-PURPOSE Interior & Exterior Water-Base Primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ 2 ALL-PURPOSE Primer.

Fire Restoration: It is critical to clean smoke damaged surfaces thoroughly before priming. Primer recommendations: Water based primers such as KILZ RESTORATION™ or oil based primers such as KILZ ORIGINAL (interior use) or KILZ ORIGINAL INTERIOR/EXTERIOR.

***WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

TEST SPECIFICATIONS:

Flexibility

ASTM D522 – Pass

Biological Growth

ASTM D3274 – Pass

COMPLIES WITH THE BELOW AS OF 1/1/2019

SCAQMD	YES	LEED®	YES
CARB	YES	MPI#	6
OTC	YES	GREENGUARD	YES
LADCO	YES	CHPS	YES
AIM	YES	NAHB/ICC NGBS	YES

*Please see www.uspb.org/LEED for additional details.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F – 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun.
- Shelf life under normal conditions is 2 years unopened.
- Partially used cans might develop skinning if not tightly sealed.

GENERAL INFORMATION:

WARNING

Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION IRRITANT Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, heading or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC -23C or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling and before smoking or eating.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.