

FROGTAPE®



EXCLUSIVE PAINTBLOCK® TECHNOLOGY MULTI-SURFACE PAINTER'S TAPE

TYPICAL APPLICATIONS

- Ideal for use on cured painted walls, wood trim, glass and metal

ADVANTAGES AND BENEFITS

- Exclusive PaintBlock Technology reacts with water-based paint and seals the edges of the tape, preventing paint bleed, resulting in very sharp paint lines
- Innovative plastic canister protects tape edges for long life
- Removes clean up to 21 days; withstands direct sunlight up to 7 days

CONSTRUCTION

Overall Grade/Function: Multi-Surface

Backing: Fine structured crepe

Adhesive: Rubber-based

COLOR(S)



Green (GRN)



STANDARD WIDTH(S)

24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness	5.7 mils	0.14 mm
Elongation	10%	10%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*FrogTape®, Keeps Paint Out. Keep Lines Sharp® and Shurtape® are registered trademarks of Shurtape Technologies, LLC

Form# TDS-CF-120-09/04/2014