

RAC X SYSTEM

Reverse-A-Clean SwitchTips



NEW!

Finally, spray tips that get the job done faster and last longer, saving time and money on every job.

INTRODUCING GRACO'S NEW LINE OF BREAKTHROUGH SPRAY TIPS.

Designed with the contractors' needs in mind, these job-specific spray tips give you long life, a superior fan pattern, and a high-quality finish.

- RAC® X SwitchTip™ has the longest-lasting fan pattern on the market and delivers 50% more life!*
- RAC X™ WideRAC™ SwitchTip delivers a 24 in (61 cm) spray pattern.
- RAC X Fine Finish SwitchTip offers superior atomization.

We took your suggestions and coupled them with the latest technological advances to bring you the best tips on the market!

THE RAC X SYSTEM - EXCEPTION

Spray better with the **New RAC X!**

Newly designed to give you exceptional results.

RAC X SwitchTip • RAC X HandTite™ Guard • OneSeal™ Gasket

- Experience breakthrough performance!
- Superior atomization
- All RAC X Airless Tips feature OneSeal design
- Maximum Working Pressure: 4050 psi (27.9 MPa, 279 bar)

Aerodynamic Design Directs the material flow, virtually eliminating paint build-up

Raised Tip Size Number Easy to read tip size, even when coated with paint!

Locking Tab

- · Ensures tip stays securely in guard
- · "Snaps" tip into spray or reverse position

Easy Turn Design

Change orientation of quard, from vertical to horizontal, without loosening the nut

Improved OneSeal Desian

- · Solvent-resistant for all coatings
- · Easier tip insertion and rotation force

Use RAC X Tips only with RAC X Guards. Not interchangeable with RAC 5 Tips.

LONGEST LASTING FAN PATTERN ON THE MARKET!

RAC X SwitchTips

LTX-XXX Blue (Odd #)

- Longest lasting fan pattern on the market!
- · Optimized for today's latex and oil-based coatings
- · Maintains a useable fan over the life of the tip — keep spraying without wasting time or material
- Sprays longer than RAC 5 or the competition
- Highest-quality finish available

Easy to assemble without tools.






Use front arrow to knockout seal for quick cleaning.


We put RAC X to the test.

G

After 60 gal (227 L) of paint, RAC X performs 52% better than the competition and 32% better than RAC 5! Spray the same area with fewer passes, saving time and labor.









Type: RAC X SwitchTips

Paint Sprayed: 60 gallons (227 L)

Fan Pattern Loss: Only 19%!

Fan pattern is still 11 in (28 cm) wide!

RAC 5 SwitchTips

Paint Sprayed: 60 gallons (227 L)

Fan Pattern Loss:

Fan pattern is

10 in (25 cm) wide.

Type:

Competitive Tips

Paint Sprayed:

60 gallons (227 L)

Fan Pattern Loss:

Fan pattern is only 6 in (15 cm) wide.

Test was conducted using Exterior Flat Latex, 2500 psi (170 bar), 1/4 in x 50 ft (6.4 mm x 15.2 m) hose and new 515 tips

FE, PATTERN AND FINISH

COMPLETE JOBS IN HALF THE TIME!

RAC X WideRAC SwitchTips

WR-XXXX Blue (Odd #)


- 24 in (610 mm) spray fan for maximum coverage
- · Finish jobs in half the time!
- Increased flow rate ensures the proper mil build
- Perfect for large jobs!
- Optimized for interior and exterior latex paint and primer




WideRAC Conversion						
RAC 5 or RAC X	WideRAC					
415 or 515	1221 or 1223					
417 or 517	1223 or 1225					
419 or 519	1225 or 1227					
521 or 621	1229 or 1231					
523 or 623	1233 or 1235					
525 or 625	1235 or 1237					


When you use WideRAC, be sure to increase the flow rate of the tip to ensure the same mil build and rate of application (arm speed).

Also, make sure your airless sprayer can support the larger tip size.



WideRAC saves you time, labor and energy!





12 in (305 mm) Pattern with Standard Tip

SUPERIOR ATOMIZATION!

New sizes now available - FFT208 - FTT308 - FFT314!

RAC X Fine Finish SwitchTips

FFT-XXX Green (Even #)

- Pre-orifice design gives you the best finish quality where you need it!
 - Trim and moldings
 - Cabinets
 - Shutters and doors
- Spray at lower pressures than standard tips and Fine Finish RAC 5 tips
- Less overspray
- Tighter, more consistent fan patterns



RAC X Tip Selection

RAC X SWITCHTIPS

Orifice Size - Inches																
	in.	(mm)	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035
_	2-4	(51-102)														
畢	4-6	(102-152)	209*	211	213	215*	217*									
Width	6-8	(152-203)	309*	311	313	315	317	319*	321*							
5	8-10	(203-254)		411	413	415	417	419	421*	423*						
Fan	10-12	(254-305)		511	513	515	517	519	521	523*	525*	527*		531*		535*
Ē	12-14	(305-356)				615*	617	619	621	623*	625*	627*	629*	631*		635*
		(356-406)							721*							
Fl	low ra	ate (gpm)	.09	.12	.18	.24	.31	.38	.47	.57	.67	.77	.90	1.03	1.17	
F	low r	ate (lpm)	.33	.49	.69	.91	1.17	1.47	1.79	2.15	2.54	2.96	3.42	3.90	4.42	
(water @ 2000 psi, 138 bar, 13.8 MPa)																

Example: for a tip with a .015 orifice and a 6 in (152 mm) pattern, order LTX315. Fan width of spray pattern is measured at 12 in (305 mm) from the surface. Fan pattern may vary depending on material sprayed.

^{*} Tip sizes will be available in the second half of 2004.



RAC X WIDERAC SWITCHTIPS

	Orifice Size - Inches										
in.	(mm)	.021	.023	.025	.027	.029	.031	.033	.035	.037	.039
24	(610)	1221	1223	1225	1227	1229	1231	1233	1235	1237	1239
Flow	rate (gpm)	.47	.57	.67	.77	.90	1.03	1.17	1.31	1.47	1.63
Flow	rate (lpm)	1.79	2.15	2.54	2.96	3.42	3.90	4.42	4.98	5.56	6.18
(water @ 2000 psi, 138 bar, 13.8 MPa)											

Example: for a tip with a .027 orifice and a 24 in (305 mm) pattern, order WR1227. Fan width of spray pattern is measured at 12 in (305 mm) from the surface. Fan pattern may vary depending on material sprayed.

RAC X FINE FINISH SWITCHTIPS

Orifice Size - Inches								
in.	(mm)	.008	.010	.012	.014			
4-6	(102-152)	208	210	212	214			
6-8	(152-203)	308	310	312	314			
8-10	(203-254)		410	412	414			
Flow	rate (gpm)	.069	.11	.15	.21			
Flow	rate (lpm)	.26	.41	.59	.80			
(water @ 2000 psi, 138 bar, 13.8 MPa)								

Example: for a tip with a .010 orifice and a 8 in (203 mm) pattern, order FFT410. Fan width of spray pattern is measured at 12 in (305 mm) from the surface. Fan pattern may vary depending on material sprayed.

Find RAC X on these Graco Accessories!

GUNS

246220	Contractor II Gun (2-finger) with RAC X 517 SwitchTip	246230	Contractor FTx II Gun (4-finger) with RAC X 515 SwitchTip	246240	Silver Plus [™] Gun with RAC X 517 SwitchTip
246221	Contractor II Gun (4-finger) with	246231	Contractor FTx II Gun (2-finger) with	246468	Flex Plus [™] Gun with

RAC X GUARDS AND ONESEALS

Use with all RAC X Tips (LTX-XXX) (WR-XXXX) (FFT-XXX)

246215 For 7/8 in (22 mm) thread size **246453** OneSeal (5-pack) **246437** 11/16 in (17 mm) thread



GUN HOSE KITS

Include the following unless otherwise noted: Airless Gun, RAC X 517 SwitchTip and HandTite Guard, 1/4 in x 50 ft (6.3 mm x 15.2 m) Blue Max™ Airless Hose and 3 ft (0.9 m) Whip Hose

287036	Contractor II Gun Hose Kit	287041	Silver Plus Gun Hose Kit
287037	Contractor II Gun Hose Kit 3/8 in x 50 ft (9.5 mm x 15.2 m) Airless Hose	287042	Silver Plus Gun Hose Kit - 3/8 in x 50 ft (9.5 mm x 15.2 m) Airless Hose 3300 psi (22.7 MPa, 227 bar)
287040	Contractor FTx II Gun Hose Kit with RAC X 517 SwitchTip	287043	Silver Plus Gun Hose Kit - 3/8 in x 50 ft (9.5 mm x 15.2 m) Airless Hose 3600 psi (24.8 MPa, 248 bar)
287095	Flex Plus Gun Hose Kit		2000 psi (24.0 ivira, 240 Dai)



TIP EXTENSIONS POLE GUNS

Includes RAC X HandTite Guard

287019 10 in (25 cm)
 287021 20 in (50 cm)

 287020 15 in (38 cm)
 287022 30 in (75 cm)

Includes RAC X 517 SwitchTip and HandTite Guard

287023 3 ft (0.9 m) **287024** 6 ft (1.8 m)

287030 CleanShot™ Shut-Off Valve

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

1800-690-2894 Fax: 1800-334-6955 or visit us at www.graco.com.

