

#### 1. Identification

Product name	:	Sika <sup>®</sup> Post Fix Part B
Supplier	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

#### 2. Hazards identification

#### **GHS Classification**

Acute toxicity, Category 4 (Inhalation) Skin irritation, Category 2 Eye irritation, Category 2B Respiratory sensitization, Category 1

Skin sensitization, Category 1 Specific target organ systemic toxicity single exposure, Category 3, Respiratory system Specific target organ systemic toxicity repeated exposure, Category 2 (Inhalation) H332: Harmful if inhaled.
H315: Causes skin irritation.
H320: Causes eye irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **GHS** label elements

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H315 + H320 Causes skin and eye irritation.

H317 May cause an allergic skin reaction. H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

Revision Date 07/25/2018



	difficulties if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary Statements :	<ul> <li>Prevention:</li> <li>P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 Wear protective gloves.</li> <li>P285 In case of inadequate ventilation wear respiratory protection.</li> <li>Response:</li> <li>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</li> <li>P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.</li> <li>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.</li> <li>P362 Take off contaminated clothing and wash before reuse.</li> <li>Storage:</li> <li>P403 + P233 Store in a well-ventilated place. Keep container tightly closed.</li> <li>P405 Store locked up.</li> <li>P501 Dispose of contents/ container to an approved waste disposal plant.</li> </ul>

See Section 11 for more detailed information on health effects and symptoms. There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### 3. Composition/information on ingredients

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 50 - < 100 %
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	>= 25 - < 50 %
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	>= 10 - < 20 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Revision Date 07/25/2018



If include	Maya ta frash air
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Clean mouth with water and drink afterwards plenty of water Do not induce vomiting without medical advice.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>Obtain medical attention.</li> </ul>
Most important symptoms and effects, both acute and delayed	<ul> <li>irritant effects sensitizing effects</li> <li>Asthmatic appearance Cough Respiratory disorder Allergic reactions Headache See Section 11 for more detailed information on health effect and symptoms.</li> <li>Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled.</li> <li>May cause allergy or asthma symptoms or breathing difficulties if inhaled.</li> <li>May cause respiratory irritation.</li> <li>May cause damage to organs through prolonged or repeate exposure if inhaled.</li> </ul>
Protection of first-aiders	<ul> <li>Move out of dangerous area.</li> <li>Consult a physician.</li> <li>Show this material safety data sheet to the doctor in attendance.</li> </ul>
Notes to physician	: Treat symptomatically.

#### 5. Fire-fighting measures

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific extinguishing	:	Collect contaminated fire extinguishing water separately. This

Revision Date 07/25/2018



methods	must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures Environmental precautions	<ul> <li>Use personal protective equipment. Deny access to unprotected persons.</li> <li>Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.</li> </ul>
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
7. Handling and storage	
Advice on safe handling	<ul> <li>Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products.</li> </ul>
Conditions for safe storage	<ul> <li>Store in original container.</li> <li>Keep in a well-ventilated place.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>
Materials to avoid	: No data available

### 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
4,4'-methylenediphenyl	101-68-8	ACGIH	TWA	0.005 ppm

Print Date 07/25/2018

Revision Date 07/25/2018

diisocyanate				
		OSHA Z-1	С	0.02 ppm 0.2 mg/m3
		OSHA P0	С	0.02 ppm 0.2 mg/m3
o-(p- isocyanatobenzyl)phenyl isocyanate (MDI)	5873-54-1	OSHA Z-1	С	0.02 ppm 0.2 mg/m3
		OSHA P0	С	0.02 ppm 0.2 mg/m3

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### \*\*<u>Basis</u>

ACGIH. Threshold Limit Values (TLV) OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values) OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant OSHA P2. Permissible Exposure Limits (PEL), Table Z-2 OSHA Z3. Table Z-3, Mineral Dust

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### Personal protective equipment

Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fe respirator complying with an approved standard if a risk assessment indicates this is necessary.	
	The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.	
Hand protection Remarks :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	
Eye protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.	
Skin and body protection :	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to	

Revision Date 07/25/2018



	the specific work-place.
Hygiene measures	<ul> <li>Avoid contact with skin, eyes and clothing.</li> <li>Wash hands before breaks and immediately after handling the product.</li> <li>Remove contaminated clothing and protective equipment before entering eating areas.</li> <li>Wash thoroughly after handling.</li> </ul>

### 9. Physical and chemical properties

Appearance	:	liquid
Color	:	brown
Odor	:	mild
Odor Threshold	:	No data available
Flash point	:	> 230 °F (110 °C)
Ignition temperature	:	No data available
Decomposition temperature	:	No data available
Lower explosion limit (Vol%)	:	No data available
Upper explosion limit (Vol%)	:	No data available
Flammability (solid, gas)	:	No data available
Oxidizing properties	:	No data available
рН	:	Note: not determined
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Vapor pressure	:	0.01 mmHg (0.01 hpa)
Density	:	1.240 g/ml at 73 °F (23 °C)
Water solubility	:	Note: insoluble
Partition coefficient: n-	:	No data available
octanol/water Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	>20.5 mm2/s at  104 °F (40 °C)
Relative vapor density	:	No data available

Revision Date 07/25/2018



Evaporation rate	: No data available	
Burning rate	: No data available	
Volatile organic compounds (VOC) content	: 0 g/l A+B Combined	

#### 10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

#### 11. Toxicological information

#### Acute toxicity

Harmful if inhaled.

#### Components:

4,4'-methylenediphenyl diisocyanate:				
Acute inhalation toxicity	: Acute toxicity estimate: 1.5 mg/l Test atmosphere: dust/mist Method: Expert judgment			

#### Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	: LD50 Oral (Rat): > 10,000 mg/kg
Acute inhalation toxicity	<ul> <li>Acute toxicity estimate: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Assessment: The component/mixture is moderately toxic after short term inhalation.</li> </ul>
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 9,400 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes eye irritation.

#### Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.





#### Germ cell mutagenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information. IARC Not applicable

NTP	Not applicable
-----	----------------

#### 12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Component:	
Diphenylmethanediisocyan 9016-87-9 ate, isomeres and homologues	Toxicity to fish: LC50Species: Brachydanio rerio (zebrafish) Dose: > 1,000 mg/l Exposure time: 96 hToxicity to algae: EC50 Species: Desmodesmus subspicatus (green algae) Dose: > 1,640 mg/l Exposure time: 72 hToxicity to daphnia and other aquatic invertebrates Chronic toxicity:
13. Disposal considerations	
Disposal methods	
Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

#### Contaminated packaging : Empty containers should be taken to an approved waste

Revision Date 07/25/2018



handling site for recycling or disposal.

#### 14. Transport information

DOT Not dangerous goods IATA Not dangerous goods IMDG Not dangerous goods

Special precautions for user No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

#### 15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Chronic Health Hazard Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposure)	
SARA 302	:	: This material does not contain any components with a section 302 EHS TPQ.	
SARA 313	:	The following components are subject to reporting levelsestablished by SARA Title III, Section 313:4,4'-methylenediphenyl101-68-853.00 %diisocyanate	

Revision Date 07/25/2018



	Diphenylmethanediisocyana te, isomeres and homologues	9016-87-9	31.00 %
Clean Air Act			
Ozone-Depletion Potential	This product neither contains Class I or Class II ODS as de Section 602 (40 CFR 82, Sub	fined by the U.S.	Clean Air Act
The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):			
	4,4'-methylenediphenyl diisocyanate	101-68-8	53.00 %
This product does not contain Accidental Release Preventior	any chemicals listed under the l n (40 CFR 68.130, Subpart F).	U.S. Clean Air Ac	t Section 112(r) for
California Prop 65	This product does not contain of California to cause cancer, defects.	•	

#### 16. Other information

**HMIS Classification** 

Health *	3
Flammability	1
Physical Hazard	0
Personal Protection	X

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT



Revision Date 07/25/2018

# BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 07/25/2018

Material number: 465181