SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: GacoFlex S42 White Solvent-Free Silicone Coating

Product Code: \$4200, \$4200-5. \$4200-55, \$4200-275

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Architectural Coating and Waterproofing

Use this product in accordance with all local, regional, national and international regulations.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Firestone Building Products

200 4th Avenue South Nashville, TN 37201

Gaco is a Firestone Building Products brand

Telephone Number: 800-331-0196 / **International:** 001-800-331-0196

Email:sds@gaco.comWebsite:www.gaco.com

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number:

For Chemical Emergency Spill, Leak, Fire, Exposure, or Incident Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

HAZARD CLASSIFICATION	CATEGORY
Flammable Liquids	4
Eye Damage/Irritation	1
Sensitization – Skin	1B
Toxic to Reproduction - fertility	2
Specific Target Organ Toxicity – (Repeated Exposure) – STOT RE	2
(Oral, Cardiovascular/Blood)	

2.2 LABEL ELEMENTS

Hazard Pictogram: GHS07; GHS08





SAFETY DATA SHEET

Signal Word: DANGER

Hazard Statement: Combustible liquid

May cause an allergic skin reaction

Causes serious eye damage Suspected of damaging fertility

May cause damage to organs (cardiovascular/blood) through prolonged or

repeated exposure (Oral)

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces/sparks/open flames/hot surfaces. -No

smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: In case of fire: Use Water fog. Foam. Dry chemical powder. Carbon dioxide

(CO2) to extinguish.

Specific treatment (see section 8 on this label). Get Medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

If skin irritation or a rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional,

national and international regulations.

2.3 ADDITIONAL INFORMATION

Main Symptoms: Prolonged exposure may cause chronic effects. Suspected of damaging

fertility. May cause damage to organs (cardiovascular/blood) through prolonged or repeated exposure (Oral). May cause allergic skin reaction. Dermatitis. Rash. Causes severe eye damage. Symptoms may include stinging,

tearing, redness, swelling, and blurred vision. Permanent eye damage

including blindness could result.

Hazards not otherwise specified: None Known

58% of the mixture consists of ingredient(s) of unknown acute toxicity

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Material	CAS No.	Weight %*
Dimethyl siloxane, hydroxy-terminated	70131-67-8	30-60%
Nepheline syenite - various grades	37244-86-5	10-30%
Titanium dioxide (dust)	13463-67-7	7-13%
Butan-2-one O,O',O"-(methylsilylidyne)trioxime	22984-54-9	1-5%
Octamethylcyclotetrasiloxane	556-67-2	1-5%
Silicon dioxide (dust)	7631-86-9	1-5%
3-(trimethoxysilyl)propylamine	13822-56-5	1-5%



SAFETY DATA SHEET

Bis(trimethoxysilylpropyl)amine	82985-35-1	0.1-1.0%
Other components below reportable levels	-	1-5%

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURES

General Information: If you feel unwell, seek medical advice (show the label where

> possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Inhalation: Move to fresh air. Call a physician if symptoms occur.

Skin: Wash skin with plenty of soap and water. Remove contaminated

> clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and bring

along these instructions.

Eye: Immediately flush eyes with plenty of water for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical attention immediately.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Prolonged exposure may cause chronic effects.

Suspected of damaging fertility.

May cause damage to organs (cardiovascular/blood) through prolonged or repeated exposure (Oral)

May cause allergic skin reaction. Dermatitis. Rash.

Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Treat symptomatically. Symptoms may be delayed.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice (show

the label or SDS where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

General Hazards: Combustible liquid.

Suitable Extinguishing Media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2)

Unsuitable Extinguishing Media:

Do not use water jet as an extinguisher as this will spread the fire.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Specific Hazards: The product is combustible, and heating may generate vapors which

may form explosive vapor/air mixtures. During fire, gases hazardous to

health may be formed.

Products of Combustion: May include, and are not limited to: oxides of carbon.

5.3 Special protective equipment and precautions for fire-fighters (PPE) Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be



SAFETY DATA SHEET

worn in case of fire.

Special fire-fighting procedures: Keep upwind of fire. Move containers from fire area if you can do

it without risk.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment: Eliminate all ignition sources (no smoking, flares, sparks, or flames in

immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.)

away from spilled material.

Methods for Cleaning-Up: Stop the flow of material, if this is without risk. Dike far ahead of spill for

later disposal. Following product recovery, flush area with water. For

waste disposal, see Section 13 of the SDS.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material,

where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later

disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface

thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see Section 13 of the

SDS.

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Safe handling advice: Keep away from open flames, hot surfaces and sources of ignition.

When using do not smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial

hygiene practices.

General hygiene advice: Ensure that medical personnel are aware of the materials(s)

involved, and take precautions to protect themselves.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep away from heat, sparks and open flame. Keep container tightly

closed. Store in a cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials

(see Section 10 of the SDS).

Specific use: Coating and waterproofing

Technical measures: Vapors may form explosive mixtures with air. All equipment used

when handling the product must be grounded. Use non-sparking

tools and explosion-proof equipment.

Incompatible materials: None known. Not soluble in water. Water will gel product.

Safe storage: Keep away from heat, sparks and open flame. Keep container tightly



SAFETY DATA SHEET

closed. Store in a cool, dry place out of direct sunlight. Store in a well-

ventilated place. Keep in an area equipped with sprinklers.

Safe packaging material: No specific recommendations.

Precautions: Do not handle, store or open near an open flame, sources of heat or

sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges.

Safe handling advice: Observe good industrial hygiene practices.

Suitable storage conditions: Keep away from heat, sparks and open flame. Keep container tightly

closed. Store in a cool, dry place out of direct sunlight. Store in a well-

ventilated place. Keep in an area equipped with sprinklers.

Handling-technical measures: Use non-sparking tools and explosion-proof equipment. All

equipment used when handling this product must be grounded.

Local and general ventilation: Provide adequate ventilation.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Control parameters: Follow standard monitoring procedures.

Exposure limits:

Nepheline syenite - various grades

OSHA:

PEL: 5 mg/m3 TQA resp

NIOSH: None

Titanium dioxide (dust)

OSHA:

PEL[†]: TWA 15 mg/m3 TWA: 15 mg/m3 total dust

(vacated) TWA: 10 mg/m3 total dust

NIOSH:

IDLH: 5000 mg/m3 REL: Ca See Appendix A

ACGIH:

TWA: 10 mg/m3

No significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints

Silicon dioxide (dust)

OSHA:

PEL[†]: TWA 20 mppcf (80 mg/m3/%SiO2) See Appendix C (Mineral Dusts)

NIOSH:

REL: TWA 6 mg/m3

No significant exposure to primary particles of silicon dioxide is thought to occur during the use of products in which silicon dioxide is bound to other materials, such as in paints.

8.2 EXPOSURE CONTROLS

Engineering measured to reduce exposure:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

levels to all acceptable level.



8.3 INDIVIDUAL PROTECTIVE MEASURES

General: Use personal protective equipment as required.

Eye protection: Wear safety glasses with side shields (or goggles) and a face shield.

Hand protection: Wear appropriate chemical resistant gloves.

Respiratory protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an

approved respirator must be worn.

Skin and body protection: Wear appropriate chemical resistant clothing.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

Control parameters: Follow standard monitoring procedures.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls: Environmental manager must be informed of all major releases.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Viscous white liquid

Color: WHITE Form: Liquid

Odor: Sweet, mild solvent
Odor Threshold: Not available

Physical State: Liquid

pH (at 20°C): Not applicable **Melting Point/Freezing Point:** Not available **Initial Boiling Point and Boiling Range:** Not available Flash Point: 169°F/76°C **Evaporation Rate:** Not available Flammability (solid, gaseous): Combustible liquid Lower Flammability/Explosive Limit: Not available **Upper Flammability/Explosive Limit:** Not available **Evaporation rate:** Not available Vapor Pressure (mm Hg @38°C): Not available

Density (lb/gal): 10.6 Relative Density/Specific Gravity: 1.27

Vapor Density:

Solubility in water/miscibility: Not soluble in water

Partition coefficient: n-octanol/water:

Auto-ignition Temperature:

Not available

Not available

Not available

Not available

Viscosity (at 25°C):

Oxidizing Properties:

None known

Explosive Properties:

Not available

VOC: <50 g/L (<0.417 lb/gal)

Solvent content - Organic:Not availableSolvent content - Water:Not availableSolvent content - Solids:95.86%Other information:Not available

Incompatibilities: None known. Not soluble in water. Water will gel product.

Not available



SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY: The product is stable and non-reactive under normal conditions of use,

storage and transport.

10.2 CHEMICAL STABILITY

Chemical stability: Material is stable under normal conditions.

Materials to avoid: The product is stable and non-reactive under normal conditions of use,

storage and transport.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Hazardous Reactions: No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID: Avoid heat, sparks, open flames and other ignition sources. Contact with

incompatible materials.

10.5 INCOMPATIBLE MATERIALS: None known. Not soluble in water. Water will gel product.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous decomposition products:

No hazardous decomposition products are known.

Hazardous Polymerization: Does not occur.

Other Information: Not available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity: May cause an allergic skin reaction. Dermatitis. Rash. Causes severe

eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Likely Routes of Exposure: Skin contact. Eye contact. Inhalation.

Eye: Causes severe eye damage. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Permanent eye damage

including blindness could result.

Skin: May cause an allergic skin reaction. Prolonged skin contact may cause

dryness, redness, or cracking.

Ingestion: Not an expected route of exposure. Expected to be a low ingestion

nazard.

Inhalation: Not an expected route of exposure. No adverse effects due to

inhalation are expected.

LD50/LC50 values relevant to this classification:

Titanium dioxide (dust

Oral mouse LD50 > 5000 mg/kg bw Oral rat LD50 > 5000 mg/kg bw Oral rat LD50 > 2000 mg/kg bw Oral rat LD50 > 11000 mg/kg bw Inhal rat LC50 3.43-5.09 mg/L air Inhal rat LC50 > 3.56 mg/L air Inhal rat LC50 > 2.28 mg/L air Inhal rat LC50 > 6.82 mg/L air 4hr Derm data waved, unjustified

Butan-2-one O,O',O"-(methylsilylidyne)trioxime

Oral rat LD50 2463 mg/kg bw



Oral rat LD50 ca. 2500mg/kg bw Derm rat LD50 > 2000 mg/kg bw

Octamethylcyclotetrasiloxane

Oral rat LD50 > 2000 mg/kg bw Oral rat LD50 > 4800 mg/kg bw Oral rat LD50 > 61440 mg/kg bw Oral mouse LD50 1700 mg/kg bw Inhal rat LC50 2,975 ppm Derm rat LD50 > 2400 mg/kg bw Derm rat LD50 > 2000 mg/kg bw

Silicon dioxide (dust)

Oral rat LD50 > 5000 mg/kg bw
Oral rat LD50 > 10,000 mg/kg bw
Oral rat LD50 > 5620 mg/kg bw
Oral mouse LD50 > 3160 mg/kg bw
Oral rat LD50 mg/kg bw
Oral rat LD50 mg/kg bw
Oral rat LD50 > 3300 mg/kg bw
Oral rat LD50 > 3300 mg/kg bw
Oral rat LD0 10,000 mg/kg bw
Inhal rat LC0 > 0.69 mg/L air no deaths
Inhal rat LC0 > 58.8 mg/L air no deaths
Derm rabbit LD50 > 2000 mg/kg bw
Derm rabbit LD50 > 5000 mg/kg bw

Calculated overall chemical acute toxicity values for this formulation:

Calculated overall Chemical Acute Toxicity Values			
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)	
>5 mg/kg (dust and mist)	>2000 mg/kg	>2000 mg/kg	

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: Based on available data, this product is not expected to cause skin

corrosion or irritation. Prolonged skin contact may cause dryness,

redness, or cracking.

Serious Eye Damage/Irritation: Causes severe eye damage. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Respiratory Sensitization: Based on available data, this product is not expected to cause

respiratory sensitization.

Skin Sensitization: May cause an allergic skin reaction.

Symptoms and Target Organs: Prolonged exposure may cause chronic effects. Suspected of damaging

fertility. May cause damage to organs (cardiovascular/blood) through prolonged or repeated exposure (Oral). May cause allergic skin

reaction. Dermatitis. Rash. Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Permanent eye damage including blindness could result.

Chronic Health Effects: Prolonged exposure may cause chronic effects. Suspected of damaging

fertility. May cause damage to organs (cardiovascular/blood) through prolonged or repeated exposure (Oral). May cause an allergic skin

reaction. Dermatitis. Rash.

Carcinogenicity: This product is not classified as a carcinogen. Due to the form of the

product, exposure to the potentially carcinogenic components is not



SAFETY DATA SHEET

expected.

Material	OSHA(O)	ACGIH(G)	NTP(N)	IARC(I)
Titanium dioxide (dust)	Not listed	A4	Not listed	2B

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS: istration NTP (N) = National Toxicology Program

OSHA (0) =Occupational Safety and Health Administration

Yes = Expected to be carcinogenic not listed = Not expected to be carcinogenic

not listed = Not expected to be carcinogenic

ACGIH (G) = American Conference of Governmental Industrial Hygienists

A1 =Confirmed human carcinogen A2 =Suspected human carcinogen A3 =Animal carcinogen

A3 =Animal carcinogen A4 =Not classifiable as a human carcinogen

A4 = Not classifiable as a human carcinogen
A5 = Not suspected as a human carcinogen
not listed = Not expected to be carcinogenic

R = Reasonably anticipated to be a carcinogen not listed = Not expected to be carcinogenic IARC (I) eliternational Agency for Research on Cancer 1 = Carcinogenic to humans

2A =Probably carcinogenic to humans 2B =Possibly carcinogenic to humans

K =Known to be a carcinogen

3 =Not classifiable as to its carcinogenicity to humans
 4 =Probably not carcinogenic to humans
 not listed = Not expected to be carcinogenic

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity: Suspected of damaging fertility.

Specific Target Organ Toxicity (STOT):

Single Exposure: Not classified as an STOT - Single Exposure.

Repeated Exposure: May cause damage to organs (Circulatory system, blood) through

prolonged or repeated (oral) exposure.

Aspiration Toxicity: Based on available data, this product is not expected to cause aspiration

toxicity.

Other Information: Not available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: The product is not classified as environmentally hazardous. However,

this does not exclude the possibility that large or frequent spills can have

a harmful or damaging effect on the environment.

Aquatic toxicity: The product is not classified as environmentally hazardous. However, this

does not exclude the possibility that large or frequent spills can have a

harmful or damaging effect on the environment.

Environmental effects: The product is not classified as environmentally hazardous. However,

this does not exclude the possibility that large or frequent spills can have

a harmful or damaging effect on the environment.

12.2 PERSISTENCE AND DEGRADABILITY

Persistence/biodegradability: The product contains substances which are not expected to be readily

biodegradable.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: No data available.

12.4 MOBILITY

Mobility:No data available.Mobility in soil:No data available.Mobility in non-soil:No data available.

12.5 OTHER ADVERSE EFFECTS

Ozone layer: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state,

provincial, and federal regulations.

Contaminated packaging: Since emptied containers may retain product residue, follow label

warnings even after container is emptied. Dispose of contents and



SAFETY DATA SHEET

container in accordance with all local, regional, national and

international regulations.

EU Codes: The Waste code should be assigned in discussion between the user, the

producer and the waste disposal company.

Residual Waste: Dispose of in accordance with local regulations. Empty containers or

liners may retain some product residues. This material and its container

must be disposed of in a safe manner (see: Disposal instructions).

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose of contents and container in accordance with all

local, regional, national and international regulations.

Waste Codes: The Waste code should be assigned in discussion between the user, the

producer and the waste disposal company.

Other disposal recommendations: None

SECTION 14: TRANSPORT INFORMATION

DOT Non-Bulk

Not hazardous for transport under exception 173.150 (f) (2,3)

DOT Bulk

UN: NA1993

Proper shipping name: Combustible liquid, n.o.s. (Dimethyl siloxane, hydroxy-terminated, Butan-2-one

O,O',O"-(methylsilylidyne)trioxime solution)

Hazard class: 3 Packing group: PG III

IMO/IMDG

Not classified as a Dangerous Goods for Transport

ICAO/IATA

Not classified as a Dangerous Goods for Transport

Reportable quantity: Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material

SECTION 15: REGULATORY INFORMATION

US Federal Regulations:

U.S. OSHA (Occupational Safety and Health Administration) Specifically Regulated Substances (29 CFR 1910.1001-1050)

No components of this product are present at concentration greater than or equal to 0.1% and are identified as a carcinogen or potential carcinogen by OSHA.

SARA/CERCLA reporting requirements:

No components of this product are found at concentrations greater than or equal to 0.1% and are subject to the SARA/CERCLA reporting requirements.

State Right-to-Know Regulations

The following components of this product are found at concentrations greater than or equal to 0.1%, subject to state Right-to-Know reporting requirements; or are found at any



concentration and are listed under California Proposition 65.

Material	California Proposition 65	Massachus etts Right- to-Know	Minnesota Employee Right-to- Know	New Jersey Community Environme ntal Hazard Right-to- Know	New Jersey Right-to- Know Substance	Pennsylvan ia Right-to- Know	Rhode Island Right-to- Know
Titanium dioxide (dust)	Cancer (airborne, unbound particles of respirable size)	Listed	Listed	Not listed	Listed	Listed	Not listed
Silicon dioxide (dust)	Not listed	Listed	Listed	Not listed	Not listed	Listed	Not listed
Zirconium dioxide	Not listed	Listed	Not listed	Not listed	Not listed	Not listed	Not listed
Toluene	Dev	Listed	Listed	Listed	Listed	Listed	Listed

California:

Proposition 65:

WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Global Inventories:

Notification status:		
US - TSCA	All substances are listed	
Canada -DSL	Not all substances are listed	
Canada - NDSL	At least 1 substance is listed	
EU - EINECS	Not all substances are listed	
EU - ELINCS	No substances are listed	
EU - NLP	No substances are listed	
Australia – AICS	All substances are listed	
China - EICSC	All substances are listed	
Japan - ENCS	Not all substances are listed	
Korea - KECI	All substances are listed	
Taiwan - NECI	All substances are listed	
New Zealand - NZloC	Not all substances are listed	
Philippine - PICCS	All substances are listed	

EU - REACH Status:

A registration number is not available for substances in this mixture as the substances are exempted from registration, the annual tonnage does not require a registration or the registration is envisioned for a later registration deadline.

HAZARD CLASSIFICATION	CATEGORY
Eye Damage/Irritation Sensitization – Skin Toxic to Reproduction - fertility Specific Target Organ Toxicity – (Repeated Exposure) – STOT RE (Oral, Cardiovascular/Blood)	1 1B 2 2

CANADA – WHMIS (Workplace Hazardous Materials Information System) Classification:

HAZARD CLASSIFICATION	CATEGORY
-----------------------	----------



Flammable Liquids	4
Eye Damage/Irritation	1
Sensitization – Skin	1B
Toxic to Reproduction - fertility	2
Specific Target Organ Toxicity – (Repeated Exposure) – STOT RE	2
(Oral, Cardiovascular/Blood)	

MEXICO:

HAZARD CLASSIFICATION	CATEGORY
Flammable Liquids	4
Skin corrosion/Irritation	3
Eye Damage/Irritation	1
Sensitization – Skin	1B
Toxic to Reproduction - fertility	2
Specific Target Organ Toxicity – (Repeated Exposure) – STOT RE	2
(Oral, Cardiovascular/Blood)	

Carcinogen Status: No data available.

SECTION 16: OTHER INFORMATION

Health:	3*
Flammability:	2
Physical:	0

NFPA 704 (National Fire Protection Association) Rating:

Health	3
Fire	2
Reactivity	0

Legend:

DOT	US Department of Transportation
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
ACGIH	American Conference of Governmental Industrial Hygienists
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
PPE	Personal Protective Equipment
RCRA	Resource Conservation and Recovery Act
CAA	Clean Air Act
SARA	Superfund Amendments and Reauthorization Act
EPCRA	Emergency Planning and Community Right-to-Know Act
WHMIS	Workplace Hazardous Materials Information System
EU	European Union
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
TSCA	US Toxic Substances Control Act (TSCA)
DSL	Canada Domestic Substance List (DSL)
NDSL	Canada Non-Domestic Substance List (NDSL)
EINECS	European Inventory of Existing Commercial Chemical Substances (EINECS)
ELINCS	European List of Notified Chemical Substances (ELINCS)
NLP	European list of No-longer Polymers (NLP)
AICS	Australian Inventory of Chemical Substances (AICS)
EICSC	China Existing Chemical Inventory - IECSC



SAFETY DATA SHEET

ENCS Japanese Existing and New Chemical Substances Inventory(ENCS)

KECI Korea Existing Chemicals Inventory(KECI)
NZIOC New Zealand Inventory of Chemicals (NZIOC)

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

HMIS Hazardous Materials Identification System
NFPA National Fire Protection Association (NFPA)

Date of Preparation: January 2, 2019

Version: 1.0

Revision Date: January 2, 2019

Disclaimer: We believe the statements, technical information and recommendations

contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the

user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Firestone Building Products

200 4th Avenue South Nashville, TN 37201

Gaco is a Firestone Building Products brand

End of Safety Data Sheet