SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: GACOROOF LIGHT TAN SILICONE

Product Code: S1670, GR1670-5

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Architectural Coating and Waterproofing

Use this product in accordance with all local, regional, national and international regulations.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Gaco Western LLC

1245 Chapman Dr.

Waukesha, WI, 53186-5942

USA

Telephone Number: 800-331-0196 / **International**: 001-800-331-0196

Email:sds@gaco.comWebsite:www.gaco.com

1.4 EMERGENCY TELEPHONE NUMBER

For Chemical Emergency Spill, Leak, Fire, Exposure, or Incident

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class:

HAZARD CLASSIFICATION	CATEGORY
Flammable Liquids	3
Eye Damage/Irritation	2A
Sensitization – Skin	1B
Toxic to Reproduction	2
Specific Target Organ Toxicity – (Repeated Exposure) – STOT RE (Cardiovascular/Blood)(Oral)	2
(

2.2 LABEL ELEMENTS

Hazard pictogram: GHS02, GHS07, GHS08



Signal word: Warning

Hazard statement: Flammable liquid and vapor

May cause an allergic skin reaction

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause damage to organs (blood, cardiovascular) through prolonged or

repeated (oral) exposure

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces/sparks/open flames/hot surfaces. -No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: In case of fire: Use water fog, foam, dry chemical powder, carbon

dioxide (CO2) to extinguish.

Get Medical advice/attention if you feel unwell. Specific treatment (see Section 8 on this label).

If on skin (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

If skin irritation or a rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional,

national and international regulations.

2.3 ADDITIONAL INFORMATION

Main symptoms: Prolonged exposure may cause chronic effects. May cause damage to organs

(blood, cardiovascular) through prolonged or repeated (oral) exposure. Suspected of damaging fertility or the unborn child. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. May cause allergic skin reaction. Dermatitis. Rash.

Hazards not otherwise specified: None Known

72.0% of the mixture consists of ingredient(s) of unknown acute toxicity

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Material	CAS No.	Weight %*
Dimethyl siloxane, hydroxy-terminated	70131-67-8	15-40%
Limestone	1317-65-3	15-40%
Distillates (petroleum), hydrotreated light	64742-47-8	10-30%
Titanium dioxide (dust)	13463-67-7	7-13%
Butan-2-one O,O',O"-(methylsilylidyne)trioxime	22984-54-9	1-5%
Silicon dioxide	7631-86-9	1-5%
Aminopropyltriethoxysilane	919-30-2	0.1-1.0%
Octamethylcyclotetrasiloxane	556-67-2	0.1-1.0%

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURES

General information: Take off all contaminated clothing immediately. Wash

contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves.

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Take off immediately all contaminated clothing. Rinse skin with

water/shower. Get medical attention if irritation develops and persists. In case of eczema or other skin disorders: Seek medical

attention and bring along these instructions.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes.

Remove contact lenses, if present and easy to do. Get medical

attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Prolonged exposure may cause chronic effects. May cause damage to organs (blood, cardiovascular) through prolonged or repeated (oral) exposure.

Suspected of damaging fertility or the unborn child.

Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

May cause allergic skin reaction. Dermatitis. Rash.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to physicians: Treat symptomatically. Symptoms may be delayed. Thermal burns:

Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue

flushing during transport to hospital.

Specific treatments: In case of accident or if you feel unwell, seek medical advice (show

the label or SDS where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

General hazards: Flammable liquid and vapor

Suitable extinguishing media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2)



Classified to the 2012 OSHA Hazard Communication Standard 29 CFR 1920.1200.

SAFETY DATA SHEET

Unsuitable extinguishing media: Do not use water jet as an extinguisher as this will spread the fire.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Specific hazards: Vapors may form explosive mixtures with air. Vapors may travel

considerable distance to a source of ignition and flash back. During fire,

gases hazardous to health may be formed.

Products of combustion: May include, and are not limited to: oxides of carbon.

5.3 Special protective equipment and precautions for fire-fighters (PPE)

Special protective equipment for fire-fighters:

In case of fire and/or explosion, do not breathe fumes. Move containers

from fire area if you can do it without risk.

Special fire-fighting procedures: Keep upwind of fire. Move containers from fire area if you can do it

without risk.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for containment: Eliminate all ignition sources (no smoking, flares, sparks, or flames in

immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.)

away from spilled material.

Methods for cleaning-up: Stop the flow of material, if this is without risk. Dike far ahead of spill for

later disposal. Following product recovery, flush area with water. For

waste disposal, see Section 13 of the SDS.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material,

where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later

disposal. Following product recovery, flush area with water.

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface

thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal,

see Section 13 of the SDS.

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Precautions for Safe handling: Vapors may form explosive mixtures with air. Do not handle or store near an

open flame, heat or other sources of ignition. Do not smoke. Take

precautionary measures against static discharges. All equipment used when

handling the product must be grounded. Use non-sparking tools and



General hygiene advice:

Classified to the 2012 OSHA Hazard Communication Standard 29 CFR 1920.1200.

SAFETY DATA SHEET

explosion-proof equipment. Provide adequate ventilation. Wear appropriate

personal protective equipment. Observe good industrial hygiene practices. Ensure that medical personnel are aware of the materials(s) involved, and

take precautions to protect themselves.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep away from heat, sparks and open flame. Prevent electrostatic charge

build-up by using common bonding and grounding techniques. Keep container

tightly closed. Store in a cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section

10 of the SDS).

Specific use: Architectural Coating and Waterproofing

Technical measures: Vapors may form explosive mixtures with air. All equipment used when

handling the product must be grounded. Use non-sparking tools and

explosion-proof equipment.

Incompatible materials: None known. Not soluble in water.

Safe storage: Store away from incompatible materials.

Safe packaging material: Keep in original container.

Precautions: Do not handle, store or open near an open flame, sources of heat or sources of

ignition. Protect material from direct sunlight. When using do not smoke. Take

precautionary measures against static discharges.

Safe handling advice: Do not handle, store or open near an open flame, sources of heat or sources of

ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges. Use personal protection

recommended in Section 8 of the SDS.

Suitable storage conditions: Keep away from heat, sparks and open flame. Keep container tightly closed.

Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place.

Keep in an area equipped with sprinklers.

Handling-technical measures: Use non-sparking tools and explosion-proof equipment. All equipment used

when handling this product must be grounded.

Local and general ventilation: Provide adequate ventilation.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Control parameters: Follow standard monitoring procedures.

Exposure limits:

Limestone (dust)

NIOSH REL: TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp) OSHA PEL: TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp)

ACGIH TLV: 2 mg/m3 (resp)

Distillates (petroleum), hydrotreated light

ACGIH: TWA 200 mg/m3

Titanium dioxide (dust)

NIOSH REL: Ca See Appendix A OSHA PEL[†]: TWA 15 mg/m3

No significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints.



Silicon dioxide (dust)

NIOSH REL: TWA 6 mg/m3

OSHA PEL†: TWA 20 mppcf (80 mg/m3/%SiO2) See Appendix C (Mineral Dusts)

8.2 EXPOSURE CONTROLS

Engineering measures to reduce exposure:

Explosion-proof general and local exhaust ventilation.

8.3 INDIVIDUAL PROTECTIVE MEASURES

General:Use personal protective equipment as required. **Eye protection:**Wear safety glasses with side shields (or goggles). **Hand protection:**Wear appropriate chemical resistant gloves.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Skin and body protection: Wear appropriate chemical resistant clothing.

Hygiene measures: When using, do not smoke. Always observe good personal hygiene

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work

clothing should not be allowed out of the workplace.

Control parameters: Follow standard monitoring procedures.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls: Environmental manager must be informed of all major releases.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Viscous tan liquid

Color: Tan
Form: Liquid
Odor: Mild S

Odor: Mild Solvent
Odor Threshold: Not available
Physical State: Liquid

pH (at 20°C): Not available **Melting Point/Freezing Point:** Not available **Initial Boiling Point and Boiling Range:** Not available Flash Point: 103°F (39.4°C) **Evaporation Rate:** Not available Flammability (solid, gaseous): Not Flammable Lower Flammability/Explosive Limit: Not available **Upper Flammability/Explosive Limit:** Not available **Evaporation rate:** Not available Vapor Pressure (mm Hg @38°C): Not available

Density (lb/gal): 9.81
Relative Density/Specific Gravity: 1.18

Vapor Density:

Solubility in water/miscibility:Not Soluble in water

Partition coefficient: n-octanol/water:Not availableAuto-ignition Temperature:Not availableDecomposition Temperature:Not available

Not available



Viscosity (at 25°C) g/L: 5500 cps **Oxidizing Properties:** Not available **Explosive Properties:** Not available VOC: < 240 g/l**Solvent content - Organic:** 0% **Solvent content - Water:** 0% Solvent content - Solids: 79.82% Other information: Not available

Incompatibilities: None known. Not soluble in water.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY The product is stable and non-reactive under normal conditions of use,

storage and transport.

10.2 CHEMICAL STABILITY

Chemical stability: Material is stable under normal conditions.

Materials to avoid: The product is stable and non-reactive under normal conditions of use,

storage and transport.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Hazardous reactions: No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID Avoid heat, sparks, open flames and other ignition sources. Contact with

incompatible materials.

10.5 INCOMPATIBLE MATERIALS None known. Not soluble in water.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous decomposition products: No hazardous decomposition products are known.

Hazardous polymerization: Does not occur.

Other information: Not available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Acute toxicity: Causes serious eye irritation. May cause an allergic skin reaction.

Dermatitis. Rash.

Likely routes of exposure: Skin contact. Eye contact. Inhalation.

Eye: Causes serious eye irritation.

Skin: May cause an allergic skin reaction. Dermatitis. Rash.

Ingestion: Not an expected route of exposure. May cause damage to organs

(blood, cardiovascular) through prolonged or repeated (oral)

exposure.

Inhalation: Not an expected route of exposure. No adverse effects due to

inhalation are expected.

LD50/LC50 values relevant to this classification:

Distillates (petroleum), hydrotreated light

Oral rat LD50 > 5000 mg/kg bw

Oral rat LD50 > 20,000 mg/kg bw Inhal rat LC50 > 5.28 mg/L air Inhal rat LC50 > 6.03 mg/L air Inhal rat LC50 > 5.2 mg/L air Inhal rat LC50 > 4.5 mg/L air Inhal rat LC50 > 4.3 mg/L air Inhal rat LC50 > 7.5 mg/L air Derm rabbit LD50 > 2000 mg/kg bw

Titanium dioxide (dust)

Oral mouse LD50 > 5000 mg/kg bw Oral rat LD50 > 2000 mg/kg bw Oral rat LD50 > 11000 mg/kg bw Inhal rat LC50 3.43-5.09 mg/L air Inhal rat LC50 > 3.56 mg/L air Inhal rat LC50 > 2.28 mg/L air

Butan-2-one O,O',O"-(methylsilylidyne)trioxime

Oral rat LD50 2463 mg/kg bw Oral rat LD50 ca. 2500mg/kg bw Derm rat LD50 > 2000 mg/kg bw

Silicon dioxide

Oral rat LD50 > 5000 mg/kg bw xxx
Oral rat LD50 > 10000 mg/kg bw
Oral rat LD50 > 5620 mg/kg bw
Oral mouse LD50 > 3160 mg/kg bw
Oral rat LD0 > 20000 mg/kg bw
Oral rat LD50 > 3300 mg/kg bw
Oral rat LD0 10000 mg/kg bw
Inhal rat LC0 > 0.69 mg/L air no deaths
Inhal rat LC0 > 58.8 mg/L air no deaths
Derm rabbit LD50 > 2000 mg/kg bw
Derm rabbit LD50 > 5000 mg/kg bw

Calculated overall chemical acute toxicity values for this formulation:

Calculated overall Chemical Acute Toxicity Values			
LC50 (inhalation) LD50 (oral) LD50 (dermal)			
>5 mg/kg (dust and mist)	>2000 mg/kg	>2000 mg/kg	

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin corrosion/irritation: Based on available data, this product is not expected to cause skin

corrosion or irritation. Prolonged skin contact may cause dryness,

redness, or cracking.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory sensitization: Based on available data, this product is not expected to cause

respiratory sensitization.

Skin sensitization: May cause an allergic skin reaction.

Symptoms and target organs: Prolonged exposure may cause chronic effects. May cause damage to

organs (blood, cardiovascular) through prolonged or repeated (oral) exposure. Suspected of damaging fertility or the unborn child. Causes serious eye irritation. Symptoms may include stinging, tearing, redness,



Classified to the 2012 OSHA Hazard Communication Standard 29 CFR 1920.1200.

SAFETY DATA SHEET

swelling, and blurred vision. May cause allergic skin reaction. Dermatitis.

Chronic health effects: Prolonged exposure may cause chronic effects. May cause damage to

organs (blood, cardiovascular) through prolonged or repeated (oral)

exposure. Suspected of damaging fertility or the unborn child.

Carcinogenicity: This product is not classified as a carcinogen. Due to the form of the

product, exposure to the potentially carcinogenic components is not

expected.

Material	OSHA(O)	ACGIH(G)	NTP(N)	IARC(I)
Titanium dioxide (dust)	Not listed	A4	Not listed	2B
Soda Lime Borosilicate Glass	Not listed	Not listed	R - inhal	3
Silica, quartz (dust)	Not listed	A2	K	1

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS: istration NTP (N) = National Toxicology Program

OSHA (O) = Occupational Safety and Health Administration

<u>ACGIH (G)</u> =American Conference of Governmental Industrial Hygienists A1 =Confirmed human carcinogen

Yes = Expected to be carcinogenic not listed = Not expected to be carcinogenic

A5 =Not suspected as a human carcinogen not listed = Not expected to be carcinogenic

A2 =Suspected human carcinogen A3 =Animal carcinogen A4 =Not classifiable as a human carcinogen K =Known to be a carcinogen

R = Reasonably anticipated to be a carcinoger

not listed = Not expected to be carcinogenic

<u>IARC (I)</u> =International Agency for Research on Cancer 1 =Carcinogenic to humans

2A =Probably carcinogenic to humans

2B =Possibly carcinogenic to humans 3 =Not classifiable as to its carcinogenicity to humans

4 =Probably not carcinogenic to humans not listed = Not expected to be carcinogenic

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (STOT):

Not classified as an STOT - Single Exposure. **Single Exposure:**

Repeated Exposure: May cause damage to organs (blood, cardiovascular) through

prolonged or repeated (oral) exposure.

Aspiration Toxicity: Based on available data, this product is not expected to cause aspiration

toxicity.

Other Information: Not available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic toxicity: The product is not classified as environmentally hazardous. However,

this does not exclude the possibility that large or frequent spills can have

a harmful or damaging effect on the environment.

The product is not classified as environmentally hazardous. However, this Aquatic toxicity:

does not exclude the possibility that large or frequent spills can have a

harmful or damaging effect on the environment.

Environmental effects: The product is not classified as environmentally hazardous. However,

this does not exclude the possibility that large or frequent spills can have

a harmful or damaging effect on the environment.

12.2 PERSISTENCE AND DEGRADABILITY

Persistence/biodegradability: The product contains substances which are not expected to be readily

biodegradable.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: No data available.

12.4 MOBILITY

Mobility: No data available. Mobility in soil: No data available. Mobility in non-soil: No data available.

Trade Name: GR1670 - GACOROOF LIGHT TAN SILICONE

January 28, 2016



12.5 OTHER ADVERSE EFFECTS

Ozone layer: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal method: This material must be disposed of in accordance with all local, state,

provincial, and federal regulations.

Contaminated packaging: Since emptied containers may retain product residue, follow label

warnings even after container is emptied. Dispose of contents and container in accordance with all local, regional, national and

international regulations.

EU codes: The Waste code should be assigned in discussion between the user, the

producer and the waste disposal company.

Residual waste: Dispose of in accordance with local regulations. Empty containers or

liners may retain some product residues. This material and its container

must be disposed of in a safe manner (see: Disposal instructions).

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose of contents and container in accordance with all

local, regional, national and international regulations.

Waste codes: D001: Waste Flammable material with a flash point <140°F(<60°C) The

Waste code should be assigned in discussion between the user, the

producer and the waste disposal company.

Other disposal recommendations: None

SECTION 14: TRANSPORT INFORMATION

DOT Non-Bulk

Not hazardous for transport under exception 173.150 (f) (2,3)

DOT Bulk

UN: UN1263

Proper shipping name: Paint

Hazard class: 3 Packing group: PG III

IMDG

UN: UN1263

Proper shipping name: Paint

Hazard class: 3 Packing group: PG III

ICAO/IATA

UN: UN1263

Proper shipping name: Paint

Hazard class: 3 Packing group: PG III

Reportable quantity: Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US Federal Regulations:

U.S. OSHA (Occupational Safety and Health Administration) Specifically Regulated Substances (29 CFR 1910.1001-1050)

No components of this product are present at concentration greater than or equal to 0.1% and are identified as a carcinogen or potential carcinogen by OSHA.

SARA/CERCLA reporting requirements:

No components of this product are found at concentrations greater than or equal to 0.1% and are subject to the SARA/CERCLA reporting requirements.

State Right-to-Know Regulations

The following components of this product are found at concentrations greater than or equal to 0.1%, subject to state Right-to-Know reporting requirements; or are found at any concentration and are listed under California Proposition 65.

Material	California Proposition 65	Massachus etts Right- to-Know	Minnesota Employee Right-to- Know	New Jersey Community Environme ntal Hazard Right-to- Know	New Jersey Right-to- Know Substance	Pennsylvan ia Right-to- Know	Rhode Island Right-to- Know
Limestone	Not listed	Listed	Listed	Not listed	Listed	Listed	Not listed
Titanium dioxide (dust)	Note listed	Listed	Listed	Not listed	Listed	Listed	Not listed
Silicon dioxide	Note listed	Listed	Listed	Not listed	Not listed	Listed	Not listed
Silica, quartz (dust)	Not listed	Listed	Listed	Listed	Listed	Listed	Not listed
Carbon Black	Cancer	Listed	Listed	Not listed	Not listed	Listed	Not listed
Toluene	Dev	Listed	Listed	Listed	Listed	Listed	Listed
Ethylbenzene	Cancer	Listed	Listed	Listed	Listed	Listed	Listed

Global Inventories:

Notification status:				
US - TSCA	All substances are listed			
Canada -DSL	All substances are listed			
Canada - NDSL	No substances are listed			
EU - EINECS	Not all substances are listed			
EU - ELINCS	No substances are listed			
EU - NLP	No substances are listed			
Australia – AICS	All substances are listed			
China - EICSC	All substances are listed			
Japan - ENCS	All substances are listed			
Korea - KECI	All substances are listed			
Taiwan - NECI	All substances are listed			
New Zealand - NZloC	Not all substances are listed			
Philippine - PICCS	All substances are listed			

EU - REACH Status:

A registration number is not available for substances in this mixture as the substances are exempted from registration, the annual tonnage does not require a registration or the registration is envisioned for a later registration deadline.

CANADA – WHMIS (Workplace Hazardous Materials Information System) Classification:

B3, D2A, D2B



MEXICO:

Hazard Classification: 2-2-0

Carcinogen Status: No data available.

SECTION 16: OTHER INFORMATION

HMIS (Hazardous Materials Identification System) rating:

Health:	2*
Flammability:	2
Physical:	0

NFPA 704 (National Fire Protection Association) rating:

Health	2
Fire	2
Reactivity	0

Legend:

DOT	US Department of Transportation
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods

ACGIH American Conference of Governmental Industrial Hygienists

NTP National Toxicology Program

IARC International Agency for Research on Cancer

PPE Personal Protective Equipment

RCRA Resource Conservation and Recovery Act

CAA Clean Air Act

SARA Superfund Amendments and Reauthorization Act
EPCRA Emergency Planning and Community Right-to-Know Act
WHMIS Workplace Hazardous Materials Information System

EU European Union

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

TSCA US Toxic Substances Control Act (TSCA)
DSL Canada Domestic Substance List (DSL)
NDSL Canada Non-Domestic Substance List (NDSL)

EINECS European Inventory of Existing Commercial Chemical Substances (EINECS)

ELINCS European List of Notified Chemical Substances (ELINCS)

NLP European list of No-longer Polymers (NLP)
AICS Australian Inventory of Chemical Substances (AICS)

EICSC China Existing Chemical Inventory - IECSC

ENCS Japanese Existing and New Chemical Substances Inventory(ENCS)

KECI Korea Existing Chemicals Inventory(KECI)

NECI Taiwan National Existing Chemical Inventory (NECI)
NZIOC New Zealand Inventory of Chemicals (NZIOC)

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

HMIS Hazardous Materials Identification System NFPA National Fire Protection Association (NFPA)



Classified to the 2012 OSHA Hazard Communication Standard 29 CFR 1920.1200.

SAFETY DATA SHEET

Date of preparation: January 28, 2016

Version: 1.0

Revision Date: January 28, 2016

Disclaimer: We believe the statements, technical information and recommendations

contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the

user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Gaco Western LLC

End of Safety Data Sheet

Trade Name: GR1670 - GACOROOF LIGHT TAN SILICONE