

Interior Clear Wood Finish

America's Finest Brushing Lacquer gives a deep rich look to interior wood



Professionals and Do-It-Yourselfers know Deft® Clear Wood Finish Lacquer is the brand they can trust for an outstanding, fast drying, and easy-to-use finish for any interior wood project. Today's professionals and enthusiasts alike continue to appreciate its "forgiving nature" and resistance to brush marks, as well as, its crystal clear finish and fast drying time.

Saves Time and Labor

- Applies easily with a brush, pad or roller.
- Won't leave brush marks.
- Self-leveling formula requires no sanding between coats.
- Dries clear and 4-times faster than conventional oil-based polyurethane.
- Fast drying and easy application makes 1-day finishing possible.
- Easy to touch-up.

Beautiful & Durable

- Delivers the professional look of fine furniture.
- Clear finish resists yellowing over time.
- Enriches finished or unfinished wood.
- Beautiful protection of interior wood, brass and silver.
- Resists alcohol, water and other common household spills.

Plenty of Uses

Clear Wood Finish provides a deep, rich finish to enhance all interior wood surfaces (except floors). It's ideal for

- Furniture
- Doors
- Trim
- Cabinets
- Paneling
- Molding
- Use on Rosewoods and other exotic hardwoods.
- Preventing tarnishing of indoor metals, such as brass and silver.

Conformance Standard

VOC compliant – lower than Federal AIM



DFT010	Gloss	Quarts, Gallons, Fives
DFT010S	Gloss	Aerosol †
DFT011	Semi-Gloss	Quarts, Gallons, Fives
DFT011S	Semi-Gloss	Aerosol †
DFT017	Satin	Quarts, Gallons, Fives
DFT017S	Satin	Aerosol †

Product Data

PRODUCT TYPE:	Nitrocellulose Lacquer
SHEEN:	DFT010 Gloss: 90+ (60°) DFT011 Semi-Gloss: 28-32 (60°) DFT017 Satin 12-18 (60°)
VOLUME SOLIDS:	18 ± 1%
WEIGHT SOLIDS:	26 ± 1%
VOC*:	<680 g/L
WEIGHT/GALLON:	7.4 – 7.6
FLASH POINT:	53°F (11.67°C)
VISCOSITY* @77°F (25°C):	18-22 sec. EZ #3 (Zahn cup)
*Product data calculated on DFT010	
COVERAGE:	Up to 500 sq. ft./gal. (46.5 sq. m/3.78L) depending on surface texture and porosity.
Wet Film Thickness:	3.0 mils
Wet Microns:	76.2
Dry Film Thickness:	0.5 mils
Dry Microns:	12.7
Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.	
DRYING TIME:	Dry time @ 77°F (25°C); 50% relative humidity.
To Touch:	30 minutes
Tack-Free:	60 minutes
To Recoat:	2 hours

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Clean all brushes and applicators with Lacquer Thinner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal on unused product. Do not pour down a drain or storm sewer.

†Patented Fanspray™ Aerosol nozzle rotates to create a more precise vertical or horizontal fan spray pattern; allows for better control, less overspray and more even coverage.



Application Information

Stir thoroughly before using. Do not shake. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheets (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Application Equipment: Apply with a brush or paint pad or aerosol. This product must not be thinned or sprayed.

Application Method: Always apply with the grain of the wood using a smooth, even stroke. Use a quality bristle brush and avoid over-brushing, since lacquers set up fast. For best results, apply thin coats three or more times. For aerosols, please refer to the product label or MSDS for safety and detailed application instructions.

General Surface Preparation

Surface must be clean and dry. Remove all loose and peeling paint, dirt, grease and any other surface contaminants.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted **NIOSH-approved** respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to

other hazardous substances that may be released during surface preparation.

BARE WOOD: Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove all dust.

Deft Clear Wood Finish can be applied direct to wood or to enhance the color of the wood, use Deft Interior Oil Based or Water Based stains.

PREVIOUSLY COATED WOOD: If the clean surface is in good condition, sand with 180 – 220 grit sandpaper. Remove all dust. Test Deft Clear Wood Finish in a small area. If it wrinkles or lifts, strip to bare wood. If the finish is damaged or deteriorated, complete removal of the finish is recommended.

RECOAT: For adequate protection two or more coats are required. For optimum performance, three or more coats are recommended. Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove dust.

Limitations of Use

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Do not apply Clear Wood Finish over varnishes, enamels or other products that dry by oxidation; it may result in lifting or wrinkling.

Not recommended for floors.

DANGER! FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. Sanding and grinding dusts may be harmful. Aspiration hazard. Can enter lungs and cause damage. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. **1-component mixtures:** formaldehyde is released during curing. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause skin sensitization. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains material that can cause target organ damage. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep away from heat, sparks and flame. Do not smoke. Do not breathe vapor or mist. Do not swallow. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THESE PRODUCTS MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. Call physician immediately.