

TECHNICAL DATA SHEET

OLD MASTERS[®] PROFESSIONAL FAST DRY WOOD STAIN

AVAILABLE SIZES: Quart (04) and Gallon (01)

PRODUCT CODES:	601 Natural/Tint Base	607 Early American	613 Fruitwood	619 Crimson Fire
	602 Golden Oak	608 Dark Mahogany	614 Pickling White	620 Vintage Burgundy
	603 Cherry	609 Cedar	615 Puritan Pine	621 Rich Mahogany
	604 Red Mahogany	610 Dark Walnut	616 Natural Walnut	
	605 Provincial	611 Special Walnut	617 Pecan	
	606 Maple	612 Spanish Oak	618 American Walnut	

PRODUCT DESCRIPTION: Old Masters[®] Fast Dry Wood Stain is designed for the professional craftsman. This high quality oil-based stain applies easily and enhances the wood's natural grain with its intensified depth of color and clarity. Its rapid dry time and superior performance allow every project to be top-coated more quickly, granting a more efficient turnaround. The low-solvent odor makes this a great alternative to lacquer stains. Experience optimal results on all interior wood surfaces such as cabinets, doors, floors,

SURFACE PREPARATION: The wood surface must be clean, dry and free from dirt, wax, or grease. Sand the wood thoroughly, first with medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag. If staining previously finished surfaces, first restore the surface to bare wood by completely removing the old finish, then follow the surface preparation directions listed above.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION: Stir well before and during use. Stain may be brushed, sprayed or wiped onto the surface. Before the stain dries, wipe off excess stain with a soft cloth. Allow stain to dry thoroughly before applying topcoat.

MIXING AND TINTING: Achieve custom colors by intermixing Fast Dry Wood Stain colors or by adding up to 14 ounces of universal or industrial colorant per gallon to any Fast Dry Wood Stain or by adding colorant to Natural/Tint Base Fast Dry Wood Stain. Natural/Tint Base Fast Dry Wood Stain may be used to lighten a Fast Dry Wood Stain color in any proportion or as a tint base to which colorant may be added for ultimate color selection. The amount of colorant added may affect performance and extend dry time.

COVERAGE: Approximately 500 square feet per gallon depending on the porosity and texture of the wood.

DRY TIME: Oil-based finishes may be applied 30 minutes after wiping. Dry times may be extended due to humidity, low temperature, lack of air movement, excess stain application or lack of penetration. Be sure surface is thoroughly dry before topcoating. Ideal drying conditions recommended are 70° to 75°F and 35 to 50% humidity.

TECHNICAL DATA SHEET

OLD MASTERS[®] PROFESSION FAST DRY WOOD STAIN

CLEAN UP: Using a cleaning solvent, such as paint thinner or mineral spirits, is recommended for clean up. The use of paint thinners or mineral spirits may violate VOC compliancy in your area. Check with your local government agencies to ensure proper compliancy.

To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

RECOMMENDED FINISH COAT: We recommend Old Masters[®] clear finishes. However, Fast Dry Wood Stain can be topcoated with virtually any finish including professional finishes such as lacquers and conversion varnishes. Wait 24 hours before topcoating with a water-based clear finish.

MAX VOC: 550 g/L (4.5 lbs/gal)

TECHNICAL DATA

SOLIDS BY WEIGHT:	35.7% to 44.9%	FLASH POINT:	102°F Tag Closed Cup
SOLIDS BY VOLUME:	29.4% to 29.6%	VISCOSITY AT 77 °:	25 to 27 sec. Ford Cup #2 15
V.O.C.:	550 grams/liter	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	30 to 60 minutes
THEORETICAL COVERAGE @ Mil DFT:	Not Applicable	VEHICLE:	Alkyd
COVERAGE @ RECOMMENDED DFT	Not Applicable	RECOMMENDED THINNER:	Do not thin. Used as packaged.
RECOMMENDED DFT PER COAT:	Not Applicable		
WEIGHT PER GALLON:	7.1 to 8.3 lbs		

Limited Warranty Since Old Masters[®] does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters[®] liability will under no circumstances exceed the replacement of the product.