



HIGH PERFORMANCE FOR DEMANDING APPLICATIONS



MEETING THE DEMANDS OF THE HARDEST WORKING PROFESSIONALS

STRONG PERMANENT BONDS

DEPENDABLE PERFORMANCE



PRODUCT SPECIFICATIONS

DESCRIPTION	SIZE	PACKAGE CODE	GTIN	CASE PACK	CASE WEIGHT (LB)	CASE DIMS (LXWXH)	CASE VOL (CU FT)	CASES PER PALLET
HEAVY DUTY								
DAP® HD MAX	9 FL OZ	0 70798 27511 9	100 70798 27511 6	12	11	8.25" X 6.3125" X 11.875"	0.36	108
DAP® HD MAX	28 FL OZ	0 70798 27512 6	300 70798 27512 3	12	33	10.875" X 8.25" X 17.125"	0.89	60
DAP® HEAVY DUTY	10 FL OZ	0 70798 27508 6	100 70798 27510 9	12	13	8.25" X 6.3125" X 11.875"	0.36	108
DAP® HEAVY DUTY	28 FL OZ	0 70798 27510 2	100 70798 27510 9	12	35	10.875" X 8.25" X 17.125"	0.89	60
ALL PURPOSE								
DAP® ALL PURPOSE	10.3 FL OZ	0 70798 27501 0	100 70798 27501 7	12	14	8.25" X 6.3125" X 11.875"	0.36	108
DAP® ALL PURPOSE	28 FL OZ	0 70798 27502 7	100 70798 27502 4	12	37	10.875" X 8.25" X 17.125"	0.89	60
PROJECT SPECIFIC								
DAP® DRYWALL	28 FL OZ	0 70798 27518 8	100 70798 27518 5	12	37	10.875" X 8.25" X 17.125"	0.89	60
DAP® FOAMBOARD	10.3 FL OZ	0 70798 27519 5	100 70798 27519 2	12	14	8.25" X 6.3125" X 11.875"	0.36	108
DAP® FOAMBOARD	28 FL OZ	0 70798 27529 4	100 70798 27529 1	12	37	10.875" X 8.25" X 17.125"	0.89	60
SUBFLOOR								
DAP® 4000 SUBFLOOR SOLVENT FORMULA	28 FL OZ	0 70798 25117 5	100 70798 25117 2	12	28	10.875" X 8.25" X 17.125"	0.89	60
DAP® 7000 SUBFLOOR LOW VOC SOLVENT	28 FL OZ	0 70798 27042 8	100 70798 27042 5	12	33	10.875" X 8.25" X 17.125"	0.89	60
DAP® 2000 SUBFLOOR LATEX FORMULA	28 FL OZ	0 70798 27515 7	100 70798 27515 4	12	34	10.875" X 8.25" X 17.125"	0.89	60



CONSTRUCTION ADHESIVES

PRODUCT CATALOG

CONSTRUCTION ADHESIVES

HD MAX PREMIUM HYBRID FORMULA

SUPERIOR DURABILITY & POWERFUL ADHESION FOR THE TOUGHEST APPLICATIONS

- Bonds Virtually Everything
- Adheres to Wet Surfaces
- Bonds in Extreme Temps
- Application Temperature Range: 0°F - 120°F
- Easy to Gun & Control
- Meets / Exceeds ASTM D3498 & C557
- VOC Compliant
- Interior / Exterior

ADHERES TO

- | | |
|----------------|-------------|
| • Aluminum | • Wood |
| • Brick | • Plywood |
| • Concrete | • PVC |
| • Drywall | • Mirror |
| • Fiber Cement | • Marble |
| • OSB | • Granite |
| • Enhanced OSB | • Stone |
| • Metal | • Foamboard |

9 FL OZ 70798 27511
28 FL OZ 70798 27512



POLYURETHANE STRENGTH



LANDSCAPE • TUB SURROUND • MIRROR, MARBLE & GRANITE

HEAVY DUTY

HIGH STRENGTH INSTANT GRAB FOR VERTICAL PROJECTS

- Strong Permanent Bond
- Application Temperature Range: 40° - 100°F
- VOC Compliant
- Interior / Exterior

ADHERES TO

- | | |
|----------------|-----------------------------------|
| • Aluminum | • Wood |
| • Brick | • Plywood |
| • Ceramic Tile | • Masonry |
| • Concrete | • Foamboard |
| • Drywall | • Other Common Building Materials |
| • OSB | |

10 FL OZ 70798 27509
28 FL OZ 70798 27510



HIGH STRENGTH INSTANT GRAB



PANELING • MOLDING • TRIM • DRYWALL & MORE

ALL PURPOSE

EASY TO CLEAN, LOW ODOR ADHESIVE FOR INDOOR PROJECTS

- Strong Permanent Bond
- Multi-Material
- Instant Grab
- Bonds Common Building Materials
- Application Temperature Range: 40° - 100°F
- VOC Compliant
- Interior

ADHERES TO

- | | |
|---------------|----------------|
| • Foamboard | • Masonry |
| • Plywood | • Wood |
| • OSB | • Concrete |
| • FRP | • Ceramic Tile |
| • ABS | • Drywall |
| • Polystyrene | • Cove Base |

10.3 FL OZ 70798 27501
28 FL OZ 70798 27502



PANELING • FOAMBOARD • COVE BASE • TRIM & MORE

DRYWALL

PROVIDES A STRONG PERMANENT BOND FOR INSTALLATION OF DRYWALL PANELS

- Prevents Nail Pops
- Limits Air & Sound Movement Between Walls
- Instant Grab Holds Panels in Place
- Application Temperature Range: 40° - 100°F
- Meets / Exceeds ASTM C557
- Easy to Gun
- VOC Compliant
- Interior

ADHERES TO

- | | |
|-----------|----------------------|
| • Plywood | • Wood |
| • OSB | • Paneling |
| • Drywall | • Metal |
| • Masonry | • Dimensional Lumber |

IDEAL FOR

- Interior Drywall
- Paneling Installation

28 FL OZ 70798 27518



FOAMBOARD

INSTANT GRAB HOLDS FOAM PANELS IN PLACE FOR EASIER INSTALLATION

- Won't Etch or Burn Through Foam Panels
- Application Temperature Range: 40° - 100°F
- Meets / Exceeds ASTM C557
- VOC Compliant
- Interior

ADHERES TO

- | | |
|-----------|----------------------------|
| • Plywood | • Concrete |
| • OSB | • Dimensional Lumber |
| • Drywall | • Polystyrene Foam |
| • Masonry | • Foam Installation Panels |
| • Wood | |

IDEAL FOR

- Polystyrene Foam
- Foam Insulation

10.3 FL OZ 70798 27519
28 FL OZ 70798 27529



4000 SUBFLOOR SOLVENT FORMULA

HIGH STRENGTH WEATHERPROOF BOND

- Bonds Wet, Frozen & Treated Lumber
- Application Temperature Range: 0° - 120°F
- Easy to Gun in Cold Temperatures
- Meets / Exceeds ASTM D3498
- Interior / Exterior

ADHERES TO

- Plywood
- OSB
- Enhanced OSB
- Masonry
- Concrete
- Treated Lumber

IDEAL FOR

- Subfloor
- Wood-to-Wood Assemblies
- Glued Floor Systems
- Deck Installation

28 FL OZ 70798 25117

HIGH STRENGTH WEATHERPROOF BOND



7000 SUBFLOOR LOW VOC SOLVENT

HIGH STRENGTH WEATHERPROOF BOND

- Bonds Wet, Frozen & Treated Lumber
- Application Temperature Range: 0° - 120°F
- Meets / Exceeds ASTM D3498
- VOC Compliant
- Interior / Exterior

ADHERES TO

- | | |
|----------------------|------------------|
| • Concrete | • Metal |
| • Dimensional Lumber | • OSB |
| • Enhanced OSB | • Plywood |
| • Masonry | • Treated Lumber |

IDEAL FOR

- Subfloor
- Wood-to-Wood Assemblies
- Glued Floor Systems
- Deck Installation

28 FL OZ 70798 27042



2000 SUBFLOOR LATEX FORMULA

STRONG DURABLE BOND

- Prevents Floor Squeaks
- Easy to Gun
- Application Temperature Range: 40° - 100°F
- VOC Compliant
- Interior / Exterior

ADHERES TO

- | | |
|------------|----------------------|
| • Plywood | • Wood |
| • OSB | • Treated Lumber |
| • Masonry | • Dimensional Lumber |
| • Concrete | |

IDEAL FOR

- Subfloor
- Wood-to-Wood Assemblies
- Glued Floor Systems
- Deck Installation

28 FL OZ 70798 27515

