



TECHNICAL DATA SHEET



Henkel Corporation
 Professional and Consumer Adhesives
 Rocky Hills, CT 06067
 Phone 1-800-624-7767
 Fax (440) 250-7863
www.henkel.com www.loctiteproducts.com

DESCRIPTION

Loctite® Polyseamseal® All-Purpose Adhesive Caulk is a premium grade water-based caulk designed to have the strength of an adhesive and the sealing characteristics of a caulk. Polyseamseal® All-Purpose bonds to almost any surface including wood, concrete, metal, ceramic, drywall, plaster and much more. Easy to apply and tool. Environmentally safe, soap and water clean-up. Contains no silicone.

RECOMMENDED FOR:

Polyseamseal® All-Purpose was designed to be a multiple use adhesive and caulk. Can be used for almost any household or remodeling project. Use for gluing loose molding or tiles, securing backsplashes, setting sinks and even repairing or concealing small cracks in plaster, drywall or around molding and baseboards. Polyseamseal® All-Purpose can even help to lower energy costs by sealing air leaks around windows and door sand other utility and plumbing penetrations.

LIMITATIONS

- Do not apply at temperatures below 40°F (5°C) and above 100°F (38°C)
- Do not apply outdoors if rain or freezing temperatures are expected within 24 hours of application
- Not recommended for continuous water immersion
- Not for use below water line, on mirrors or in aquariums, under shower door tracks or between two non-porous surfaces
- Not for use in architectural joints, joints subject to heavy abrasion or wear or tuck pointing
- If joint size exceeds ¼" x ¼" use backing material
- Not for use on Butt joints
- Do not use on unfinished or unprimed fiber cement (Fiber cement must be primed or have a factory finish before application)

FEATURES & BENEFITS:

Feature	Benefits
2-in-1 product.....	Possesses both bonding and sealing capabilities
Permanently flexible and durable.....	Long lasting, professional finish
Mold & mildew resistant.....	Inhibits mold & mildew growth
Easy clean up.....	Uncured adhesive cleans up easily with soap and water
Water-resistant.....	Ideal for humid or steamy areas
Paintable and durable.....	Long lasting, professional finish
Water-based product.....	Low odor, non-toxic, non-flammable

COVERAGE

- For a ¼" (6 mm) bead:
- A 1.5 fl. oz. (44 mL) squeeze tube will extrude approx. 4.6 ft. (1.4 m)
 - A 5.5 fl. oz. (163 mL) squeeze tube will extrude approx. 16.9 ft. (5.1 m)
 - A 10 fl. oz. (295 mL) cartridge will extrude approx. 30.6 ft. (9.3 m)



Color	Size	Packaging	Item #
White	1.5 oz.	Squeeze Tube	1515888
	5.5 oz.	Squeeze Tube	1515864
	5.5 oz.	Squeeze Tube	1515882
	5.5 oz.	Squeeze Tube	1515770
	10 oz.	Plastic Cartridge	1515133
	10 oz.	Plastic Cartridge	1514750
	10 oz.	Plastic Cartridge	1515136
Clear	5.5 oz.	Squeeze Tube	1508193
	5.5 oz.	Squeeze Tube	1508196
	10 oz.	Plastic Cartridge	1507601
	10 oz.	Plastic Cartridge	1508194
	10 oz.	Plastic Cartridge	1508195
Almond	10 oz.	Plastic Cartridge	1515146
	10 oz.	Plastic Cartridge	1515145
Black	10 oz.	Plastic Cartridge	1515170

DIRECTIONS

Tools Typically Required:

Utility knife, caulking gun, masking tape and tooling device.

Safety Precautions:

Apply and cure in a well ventilated area. Wear gloves and wash hands after use.

Preparation:

Apply sealant between 40°F (5°C) and 100°F (38°C). Surfaces must be clean, dry and free of old caulk, grease, dust and other contaminants. Remove mold or mildew using bleach and detergent that does not contain ammonia. Rinse surface and allow to dry. For neat bead lines, mask both sides of the joint. Cut the tip off the cartridge or squeeze tube at a 45° angle to desired bead size (minimum of 1/8").

Application:

Apply sealant with steady pressure, forcing the sealant into the joint. Smooth bead immediately with a wet finger or a tool. Remove masking tape immediately after tooling and wipe excess off of hands and tools. Sealant is paintable within 2 hours depending on temperature and humidity. Allow at least 24 hours before exposing to water. Periodically clean cured sealant with non-abrasive cleaner for best appearance. Note: The clear product will extrude white and will turn clear as it dries.

Clean-up

Clean tools and sealant residue immediately with warm water and soap. Cured sealant may be carefully cut away with a sharp-edged tool.

STORAGE & DISPOSAL

DAMAGED BY FREEZING. To maximize shelf life, store cartridge in a cool, dry place at temperatures above 40°F (5°C) and below 100°F (38°C). Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.

PRECAUTIONS

CAUTION! Wash hands after handling. Avoid contact with eyes and skin. Do not take internally. If swallowed, seek medical attention immediately. Keep from freezing. KEEP OUT OF THE REACH OF CHILDREN.

Refer to Material Safety Data Sheet (MSDS) for further information.

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
<u>Color:</u>	White, Almond and Black (Note: Clear product will extrude white and change to clear as it dries.)	<u>Application Temperature:</u>	Apply between 40°F (5°C) and 100°F (38°C)
<u>Appearance:</u>	Lump-free, non-sag paste	<u>Skin Time:</u>	6 minutes
<u>Odor:</u>	Mild acrylic odor	<u>Tooling Time:</u>	10 to 20 minutes
<u>VOC Content:</u>		<u>Cure Time:</u>	24 hours to 2 weeks (Cure time is dependent on temperature, humidity and amount of product used.)
Clear (5.5 oz. & 10 oz.):	1 wt% or 15 g/L		
White			
1.5 oz. & 5.5 oz.:	1.15 wt% or 152 g/L		
10 oz.:	1.14 wt% or 142 g/L		
Almond (10 oz.):	1.16 wt% or 143 g/L		
Black (10 oz.):	1.15 wt% or 143 g/L		
<u>Shelf Life:</u> (From date of manufacture, unopened)			
1.5 oz. & 5.5 oz.:	18 months		
10 oz.:	24 months		

Lot Code Explanation: YYDDD
YY = Last two digits of year of manufacture
Cartridge: Stamped on bottom edge of cartridge body; DDD = Day of manufacture based on 365 days in a year
Squeeze Tube: Imprinted on crimped edge of tube near hang hole. For example: 09061
= 61st day of 2009
= March 2, 2009

Typical Cured Performance Properties

Color: White, Clear, Almond & Black
Service Temperature: -15°F (-26°C) to 170°F (77°C)
Paintable: Yes, after 2 hours with a latex or oil-based paint.
Water Resistant : Wait until sealant is fully cured before exposing to water (24 to 48 hours).